

FILA

driver included



Arcluce Code **0483004A+840+21**
 Ex Code **P8282-21 CEI**
 EAN Code **8054378098208**



TECHNICAL INFORMATION

Light source:	LED, 4000K, 17W, 2150lm, CRI>80
Light efficiency:	105lm/W
Power luminaire:	20W, 2100lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optic:	narrow 12°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: 111mm B: 93mm C: 621mm

CE


IP66

IK08



0,07m²

850°



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

Installation

- Wall mounted.
- Double M20 cable gland for through wiring.
- Die cast aluminium (EN 47100) or galvanized and painted steel support bracket.
- Hidden springs on extruded aluminium frame.
- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

