

FILA

driver included



Arcluce Code **0483007A+840+21**
 Ex Code **P8243-21 CEI**
 EAN Code **8054378156625**



TECHNICAL INFORMATION

Light source: LED, 4000K, 34W, 4300lm, CRI>80

Light efficiency: 63lm/W

Power luminaire: 40W, 2500lm

LED life time: > 50000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optic: ultra wide flood 135°x140°

Color: Aluminium - 21

Weight: 7 kg

Size: A: 111mm
 B: 93mm
 C: 1221mm




IP66



0,14m²



850°



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

Installation

- Wall mounted.
- Double M20 cable gland for through wiring.
- Die cast aluminium (EN 47100) or galvanized and painted steel support bracket.
- Hidden springs on extruded aluminium frame.
- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

