

# FILA

driver included



Arcluce Code **0483009A+840+21**  
 Ex Code **P8273-21 CEI**  
 EAN Code **8033765674768**



## TECHNICAL INFORMATION

**Light source:** LED, 4000K, 34W, 4300lm, CRI>80

**Light efficiency:** 100lm/W

**Power luminaire:** 40W, 4000lm

**LED life time:** > 50000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz


**Wiring:** ON/OFF

**Optic:** flood 27°

**Color:** Aluminium - 21

**Weight:** 7 kg

**Size:** A: 111mm  
 B: 93mm  
 C: 1221mm



CE

IP66



0,14m<sup>2</sup>



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

## Installation

- Wall mounted.
- Double M20 cable gland for through wiring.
- Die cast aluminium (EN 47100) or galvanized and painted steel support bracket.
- Hidden springs on extruded aluminium frame.
- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

