

# FILA

driver included



Arcluce Code **0483010A+840+21**  
 Ex Code **P8283-21 CEI**  
 EAN Code **8054378098222**



## TECHNICAL INFORMATION

<b>Light source:</b>	LED, 4000K, 34W, 4300lm, CRI>80
<b>Light efficiency:</b>	105lm/W
<b>Power luminaire:</b>	40W, 4200lm
<b>LED life time:</b>	> 50000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optic:</b>	narrow 12°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	7 kg
<b>Size:</b>	A: 111mm B: 93mm C: 1221mm

CE


IP66

IK08



0,14m<sup>2</sup>

850°



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

## Installation

- Wall mounted.
- Double M20 cable gland for through wiring.
- Die cast aluminium (EN 47100) or galvanized and painted steel support bracket.
- Hidden springs on extruded aluminium frame.
- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

