

# FILA

driver included - RGB DMX



Arcluce Code      **0483017F+21**  
 Ex Code            **Z8332-21 DMX**  
 EAN Code          **8054378305276**



## TECHNICAL INFORMATION

<b>Light source:</b>	LED RGB, 40W
<b>Light efficiency:</b>	31lm/W
<b>Power luminaire:</b>	40W, 1250lm
<b>LED life time:</b>	> 50000h - L80 - B20 (Ta 25°C)
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	DMX
<b>Optic:</b>	flood 30°
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	7 kg
<b>Size:</b>	A: 111mm B: 93mm C: 1221mm

CE


IP66

IK08



0,14m<sup>2</sup>

850°



## Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

## Installation

- Wall mounted.
- Double M20 cable gland for through wiring.
- Die cast aluminium (EN 47100) or galvanized and painted steel support bracket.
- Hidden springs on extruded aluminium frame.
- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.