



LUNIO-STREET

lunio-street

Arcluce Code **0877013A-840-21**

Ex Code

Code EAN **8054378339509**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	35W, 3600lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type II
Color:	Aluminium - 21
Weight:	11.5 kg
Size:	A: Ø 520mm B: 140mm C: 700mm

CE

IP66

IK08

0,16m²

0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-13.


LUNIO-STREET

lunio-street

Arcluce Code **0877013A-840-21**

Ex Code

Code EAN **8054378339509**



Specifications

Urban lighting between innovation and efficiency. Elegant and functional lighting solution, LUNIO Street is the pole top luminaire for urban lighting provided with high performance optics that generate a light perfectly directed on the street, without producing light pollution. It can be equipped with the latest technologies for smart lighting and energy efficiency.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass.

It complies with standards EN 60598-1 and EN 60598-2-13.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Brand ARCLUCE mod. LUNIO-STREET