

Urban lighting

# LUNIO7





### LUMINAIRE




- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges up to 4kV.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-3.

### INSTALLATION

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems.  
For the various possibilities, please see section "Controlling the light".

**Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.**

| STANDARD PRODUCT |  | AVAILABLE OPTIONS   |  |
|------------------|--|---|--|
| Wiring           | ON/OFF (A)   | DALI (B), BIP (E)   |  |
| CCT              | 4000K (-840)   | 3000K (-830)  |  |
| Colour           |  21 |  12,  16 |  |



Urban lighting


# LUNIO7



STANDARD COLOUR



DIMENSIONS



| Code            | Optic     | Luminaire   | CCT   | CRI | Class | Wiring | Power Supply     | A mm | B mm | C mm |
|-----------------|-----------|-------------|-------|-----|-------|--------|------------------|------|------|------|
| 0876007A-840-21 | type II   | 35W, 3600lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |
| 0876011A-840-21 | type II   | 69W, 7300lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |
| 0876013A-840-21 | type III  | 35W, 3900lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |
| 0876017A-840-21 | type III  | 69W, 8000lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |
| 0876003A-840-21 | type IV   | 35W, 3600lm | 4000K | 80  | ☐     | ON/OFF | 220-240V/50-60Hz | 520  | 627  | -    |
| 0876004A-840-21 | type IV   | 70W, 7200lm | 4000K | 80  | ☐     | ON/OFF | 220-240V/50-60Hz | 520  | 627  | -    |
| 0876001A-840-21 | type VS-W | 35W, 3300lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |
| 0876005A-840-21 | type VS-W | 69W, 6500lm | 4000K | 80  | ☐     | ON/OFF | 220-240V 50/60Hz | 520  | 627  | -    |

The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.



**Available on request:**  
versions with Future-Proof, see pag. 352.



For post top mounting, check all available solutions on page 354.

