



- NOTES:**
1. POLES DESIGNED IN ACCORDANCE WITH BCA, AS4100:1998, AS/NZS 1170.2 2002, AS 1798:1992, AS/NZS 4676:2000, AS/NZS 4677:2000
 2. HOT ROLLED STEEL FLAT PRODUCTS CONFORM TO AS 1594
 3. HOT ROLLED STEEL BARS AND SECTIONS CONFORM TO AS 3679
 4. WELDING OF STEEL STRUCTURES CONFORM TO AS/NZS 1554.1:2004
 5. ALL STEEL ITEMS FULLY HOT DIP GALVANISED AFTER FABRICATION TO AS/NZS 4680:2006
 6. HOT ROLLED STEEL PLATES CONFORM TO AS3678
 7. ALL DIMENSIONS ARE IN MILLIMETRES
 8. ALL INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE

ITEM	NAME	DESCRIPTION	MATERIAL	QTY	NOTES
1	SECTION A	WALL THICKNESS = 3MM	Grade 50	1	
2	DOOR	WALL THICKNESS = 3MM	Grade 50	1	CUT FROM POLE
3	M8X25	HEX SOCKET	Stainless Steel	2	WITH FLAT HEAD
4	M8 WASHER	BLACK	Plastic	2	FOR ITEM 3
5	M8X30	2 NUT, 2 WASHER	Copper	1	EARTHING LUG



CODE: ADPTR06.0M600D

6M POLE TAPERED ROUND WITH ACCESS DOOR AND 60MM OD SPIGOT

WEIGHT: 65KG
 REVISION DATE: 29 08 2023

ADVANCED LIGHTING TECHNOLOGIES
 110 LEWIS ROAD WANTIRNA SOUTH VIC 3152
 03 9800 5600 | ADLT.COM.AU