

Advanced Lighting Technologies are pleased to advise the following products are listed on the National Electricity Market Load Tables For Unmetered Connection Points, as published by the Australian Energy Market Operator (AEMO). Contact us for more information.

CREE LIGHTING SYRIUS (25W)*



MODEL	VARIANTS
WATTAGE:	25W
NOMINAL FLUX:	3,600 - 4,110 LUMENS
OPTICS:	TYPE II SHORT 1.0 / TYPE II SHORT
CCT:	2700K (80 CRI) / 3000K (70 CRI) / 3000K (80 CRI) / 4000K (70 CRI) / 4000K (80 CRI)
INSULATION:	CLASS 1 / CLASS 2
WIRING:	1-10V DIMMABLE / DALI / NONE
VOLTAGE:	220-240V AC
COLOUR:	SILVER/SILVER, BLACK/BLACK, SILVER/BLACK, BLACK/SILVER, WHITE/WHITE

CREE LIGHTING SYRIUS (40W)*

MODEL	VARIANTS
WATTAGE:	40W
NOMINAL FLUX:	5,500 - 6,300 LUMENS
OPTICS:	TYPE II SHORT 1.0 / TYPE II SHORT
CCT:	2700K (80 CRI) / 3000K (70 CRI) / 3000K (80 CRI) / 4000K (70 CRI) / 4000K (80 CRI)
INSULATION:	CLASS 1 / CLASS 2
WIRING:	1-10V DIMMABLE / DALI / NONE
VOLTAGE:	220-240V AC
COLOUR:	SILVER/SILVER, BLACK/BLACK, SILVER/BLACK, BLACK/SILVER, WHITE/WHITE



CREE LIGHTING XSPM - VERSION E



MODEL	VARIANTS
WATTAGE:	58W
NOMINAL FLUX:	7,200 - 7,600 LUMENS
OPTICS:	2LG / 275 / 210 / 2SH / 3SH / 3ME / 4ME
CCT:	2700K / 3000K / 4000K / 5700K
INSULATION:	CLASS 1
VOLTAGE:	220-240V AC
COLOUR:	SILVER / BLACK

CREE LIGHTING XSP - VERSION E (SINGLE MODULE)

MODEL	VARIANTS
WATTAGE:	94W
NOMINAL FLUX:	11,700 - 12,400 LUMENS
OPTICS:	2LG / 275 / 210 / 2SH / 3SH / 3ME / 4ME
CCT:	2700K / 3000K / 4000K / 5700K
INSULATION:	CLASS 1
VOLTAGE:	220-240V AC
COLOUR:	SILVER / BLACK



Advanced Lighting Technologies are pleased to advise the following products are listed on the National Electricity Market Load Tables For Unmetered Connection Points, as published by the Australian Energy Market Operator (AEMO). Contact us for more information.

CREE LIGHTING LEDWAY (LIMITED STOCK AVAILABLE)

VARIANTS	
20 LED (26W / Drive Current 350mA)	20 LED (24.3W / Drive Current 350mA)*
20 LED (48.7W / Drive Current 700mA)	40 LED (46.3W / Drive Current 350mA)*
30 LED (40.8W / Drive Current 350mA)	40 LED (69.4W / Drive Current 525mA)*
40 LED (47W / Drive Current 350mA)	80 LED (137.6W / Drive Current 525mA)*
60 LED (73.2W / Drive Current 350mA)	120 LED (196.2W / Drive Current 525mA)*
80 LED (143W / Drive Current 525mA)	120 LED (260W / Drive Current 700mA)*
120 LED (281W / Drive Current 700mA)	



CREE LIGHTING XSP - VERSION E (DOUBLE MODULE) (LIMITED STOCK AVAILABLE)



MODEL	VARIANTS
WATTAGE:	128W
NOMINAL FLUX:	17,700 - 18,800 LUMENS
OPTICS:	2LG / 275 / 210 / 2SH / 3SH / 3ME / 4ME
CCT:	2700K / 3000K / 4000K / 5700K
INSULATION:	CLASS 1
VOLTAGE:	220-240V AC
COLOUR:	SILVER / BLACK