

Urban lighting

**CONO**  
CATENARY



### LUMINAIRE

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges up to 4kV.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-3.

### INSTALLATION

- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

STANDARD PRODUCT		AVAILABLE OPTIONS	
Wiring	ON/OFF (A)	DALI (B), BIP (E)	
CCT	4000K (-840)	3000K (-830)	
Couleur	<input type="radio"/> 21	<input type="radio"/> 16	



Photorealistic rendering.

Urban lighting

# CONO


## CATENARY







## STANDARD COLOUR

 21


## DIMENSIONS




Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0883006A-840-21	 type I	35W	3650lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883007A-840-21	 type III	35W	3850lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883004A-840-21	 type VS-M	35W	4100lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883005A-840-21	 type VS-W	35W	3600lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470





 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.


## STANDARD COLOUR

 21


## DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0883014A-840-21	 type I	35W	3100lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883015A-840-21	 type III	35W	3400lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883012A-840-21	 type VS-M	35W	2750lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470
0883013A-840-21	 type VS-W	35W	3800lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	300	330	470

 The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.



Photorealistic rendering.