



CONO Catenary



performance

Arcluce Code **0883004A-840-21**
 Ex Code **S6411-21 CEI**
 Code EAN **8054378342264**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	117lm/W
Luminaire:	35W , 4100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS-M
Color:	Aluminium - 21
Weight:	7 kg
Size:	A: Ø 300mm B: 330mm C: 470mm



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



CONO Catenary

performance

Arcluce Code **0883004A-840-21**
Ex Code **S6411-21 CEI**
Code EAN **8054378342264**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary

CONO Catenary



performance

Arcluce Code **0883005A-840-21**
Ex Code **S6413-21 CEI**
Code EAN **8054378342387**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	35W , 3600lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS-W
Color:	Aluminium - 21
Weight:	7 kg
Size:	A: Ø 300mm B: 330mm C: 470mm



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



CONO Catenary

performance

Arcluce Code **0883005A-840-21**
Ex Code **S6413-21 CEI**
Code EAN **8054378342387**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary

CONO Catenary




performance

Arcluce Code **0883006A-840-21**
 Ex Code **S6415-21 CEI**
 Code EAN **8054378342509**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	104lm/W
Luminaire:	35W , 3650lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type I
Color:	Aluminium - 21
Weight:	7 kg
Size:	A: Ø 300mm B: 330mm C: 470mm



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



CONO Catenary

performance

Arcluce Code **0883006A-840-21**
Ex Code **S6415-21 CEI**
Code EAN **8054378342509**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 104lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary

CONO Catenary



performance

Arcluce Code **0883007A-840-21**
 Ex Code **S6417-21 CEI**
 Code EAN **8054378342622**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	110lm/W
Luminaire:	35W , 3850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type III
Color:	Aluminium - 21
Weight:	7 kg
Size:	A: Ø 300mm B: 330mm C: 470mm



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



CONO Catenary

performance

Arcluce Code **0883007A-840-21**
Ex Code **S6417-21 CEI**
Code EAN **8054378342622**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 110lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary



CONO Catenary

comfort

Arcluce Code **0883012A-840-21**

Ex Code

Code EAN **8054378343223**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 79lm/W

Luminaire: 35W , 2750lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type VS-M

Color: Aluminium - 21

Weight: 7 kg

Size:
A: Ø 300mm
B: 330mm
C: 470mm

CE

IP66



IK08



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




CONO Catenary

comfort

Arcluce Code **0883012A-840-21**

Ex Code

Code EAN **8054378343223**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 79lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary



CONO Catenary

comfort

Arcluce Code **0883013A-840-21**

Ex Code

Code EAN **8054378343346**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 109lm/W

Luminaire: 35W , 3800lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type VS-W

Color: Aluminium - 21

Weight: 7 kg

Size:
A: Ø 300mm
B: 330mm
C: 470mm

CE

IP66



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




CONO Catenary

comfort

Arcluce Code **0883013A-840-21**

Ex Code

Code EAN **8054378343346**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 109lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary



CONO Catenary

comfort

Arcluce Code **0883014A-840-21**

Ex Code

Code EAN **8054378343469**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 89lm/W

Luminaire: 35W , 3100lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type I

Color: Aluminium - 21

Weight: 7 kg

Size:
A: Ø 300mm
B: 330mm
C: 470mm

CE

IP66



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




CONO Catenary

comfort

Arcluce Code **0883014A-840-21**

Ex Code

Code EAN **8054378343469**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 89lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary



CONO Catenary

comfort

Arcluce Code **0883015A-840-21**

Ex Code

Code EAN **8054378343582**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 97lm/W

Luminaire: 35W , 3400lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type III

Color: Aluminium - 21

Weight: 7 kg

Size:
A: Ø 300mm
B: 330mm
C: 470mm

CE

IP66

IK08



0,09m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Catenary installation on passing cable Ø max 12mm.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




CONO Catenary

comfort

Arcluce Code **0883015A-840-21**

Ex Code

Code EAN **8054378343582**



Specifications

Classic modern urban lighting CONO is the LED fixture for urban lighting with an iconic design: the catenary version has a particular vocation for enhancing historical centres and pedestrian areas of classic taste. The radial or street optics available allow a proper illumination of different types of urban areas, avoiding light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 97lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Catenary installation on passing cable Ø max 12mm. Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. CONO Catenary