

DEMO-EVO


DEMO-EVO1



Arcluce Code **0205000A-930-11**

Ex Code

Code EAN **8054378412592**




Technical information

Light source:	LED, 3000K
Luminaire efficacy:	92lm/W
Luminaire:	12W , 1100lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 34°
UGR:	<19
Color:	White - 11
Weight:	0.23 kg
Size:	A: Ø 60mm B: 110mm

CE

IP20



Appliance

- Extruded aluminium body.
- Louvre in turned aluminum or technopolymer.
- Polyester powder paint resistant to UV rays.
- High vacuum metallized plastic reflector or optical polymer lenses.
- Long LED life time > 50000h.

Installation

- Ceiling installation.
- Grommet for single cable entry.
- Base plate made of painted steel.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

DEMO-EVO

DEMO-EVO1



Arcluce Code **0205000A-930-11**

Ex Code

Code EAN **8054378412592**



Specifications

Essentiality and lighting performance meet in this versatile ceiling-mounted luminaire for interior lighting. Perfect in situations where comfortable light, serves the environment and the person. This is the perfect luminaire when diffused, comfortable light is at the service of the environment and people.

Extruded aluminium body. Louvre in turned aluminum or technopolymer. Polyester powder paint resistant to UV rays. High vacuum metallized plastic reflector or optical polymer lenses. Long LED life time > 50000h.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 92lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Grommet for single cable entry. Base plate made of painted steel.

Brand ARCLUCE mod. DEMO-EVO

DEMO-EVO


DEMO-EVO2



Arcluce Code **0205001A-930-11**

Ex Code

Code EAN **8054378412622**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	67lm/W
Luminaire:	18W , 1200lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
UGR:	<19
Color:	White - 11
Weight:	0.51 kg
Size:	A: Ø 80mm B: 130mm

CE

IP20



Appliance

- Extruded aluminium body.
- Louvre in turned aluminum or technopolymer.
- Polyester powder paint resistant to UV rays.
- High vacuum metallized plastic reflector or optical polymer lenses.
- Long LED life time > 50000h.

Installation

- Ceiling installation.
- Grommet for single cable entry.
- Base plate made of painted steel.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

DEMO-EVO

DEMO-EVO2



Arcluce Code **0205001A-930-11**

Ex Code

Code EAN **8054378412622**



Specifications

Essentiality and lighting performance meet in this versatile ceiling-mounted luminaire for interior lighting. Perfect in situations where comfortable light, serves the environment and the person. This is the perfect luminaire when diffused, comfortable light is at the service of the environment and people.

Extruded aluminium body. Louvre in turned aluminum or technopolymer. Polyester powder paint resistant to UV rays. High vacuum metallized plastic reflector or optical polymer lenses. Long LED life time > 50000h.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 67lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Grommet for single cable entry. Base plate made of painted steel.

Brand ARCLUCE mod. DEMO-EVO

DEMO-EVO



DEMO-EVO3



Arcluce Code **0205002A-930-11**

Ex Code

Code EAN **8054378412639**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	77lm/W
Luminaire:	24W , 1850lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 30°
UGR:	<19
Color:	White - 11
Weight:	0.75 kg
Size:	A: Ø 100mm B: 155mm

CE

IP20



Appliance

- Extruded aluminium body.
- Louvre in turned aluminum or technopolymer.
- Polyester powder paint resistant to UV rays.
- High vacuum metallized plastic reflector or optical polymer lenses.
- Long LED life time > 50000h.

Installation

- Ceiling installation.
- Grommet for single cable entry.
- Base plate made of painted steel.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

DEMO-EVO

DEMO-EVO3



Arcluce Code **0205002A-930-11**

Ex Code

Code EAN **8054378412639**



Specifications

Essentiality and lighting performance meet in this versatile ceiling-mounted luminaire for interior lighting. Perfect in situations where comfortable light, serves the environment and the person. This is the perfect luminaire when diffused, comfortable light is at the service of the environment and people.

Extruded aluminium body. Louvre in turned aluminum or technopolymer. Polyester powder paint resistant to UV rays. High vacuum metallized plastic reflector or optical polymer lenses. Long LED life time > 50000h.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 77lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Grommet for single cable entry. Base plate made of painted steel.

Brand ARCLUCE mod. DEMO-EVO

DEMO-EVO

DEMO-EVO4



Arcluce Code **0205003A-930-11**

Ex Code

Code EAN **8054378412653**




Technical information

Light source:	LED, 3000K
Luminaire efficacy:	84lm/W
Luminaire:	35W , 2950lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 31°
UGR:	<19
Color:	White - 11
Weight:	1.43 kg
Size:	A: Ø 150mm B: 180mm

CE

IP20



Appliance

- Extruded aluminium body.
- Louvre in turned aluminum or technopolymer.
- Polyester powder paint resistant to UV rays.
- High vacuum metallized plastic reflector or optical polymer lenses.
- Long LED life time > 50000h.

Installation

- Ceiling installation.
- Grommet for single cable entry.
- Base plate made of painted steel.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

DEMO-EVO

DEMO-EVO4



Arcluce Code **0205003A-930-11**

Ex Code

Code EAN **8054378412653**



Specifications

Essentiality and lighting performance meet in this versatile ceiling-mounted luminaire for interior lighting. Perfect in situations where comfortable light, serves the environment and the person. This is the perfect luminaire when diffused, comfortable light is at the service of the environment and people.

Extruded aluminium body. Louvre in turned aluminum or technopolymer. Polyester powder paint resistant to UV rays. High vacuum metallized plastic reflector or optical polymer lenses. Long LED life time > 50000h.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 84lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Grommet for single cable entry. Base plate made of painted steel.

Brand ARCLUCE mod. DEMO-EVO