


# DOT opal screen

## Arcluce Code Ex Code Code EAN

### 0277003A-840-11 P7741-11 CEI 8054378189043





recimical information	
Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	63lm/W
Luminaire:	20W , 1260lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consisten	cy: < 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	extra wide flood 130°
Color:	White - 11
Weight:	1.3 kg
Size:	A: 209mm B: 89mm



### Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Opal PMMA screen.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Wall or ceiling installation.
- Grommet for single cable entry.
- Available double cable gland version for through wiring on request.

#### Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

#### Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.





ADVANCED LIGHTING TECHNOLOGIES NEW ZEALAND LTD

REVISION DATE: 21 02 2023





CE

**IP65** 

×3 IK08



# DOT opal screen





#### Arcluce Code 0277003A-840-11 Ex Code P7741-11 CEI Code EAN 8054378189043

#### Specifications



Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Opal PMMA screen. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 63Im/W Luminaire in insulation class I. DRIVER INCLUDED. Wall or ceiling installation. Grommet for single cable entry. Available double cable gland version for through wiring on request. Available versions with Casambi and other modern control systems, for more information see "Light controls" section. Brand ARCLUCE mod. DOT