


DUEDIECI

duedieci




Arcluce Code **0684010A-830-16**
 Ex Code **W8850-16 CEI**
 Code EAN **8054378208867**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	90lm/W
Luminaire:	21W , 1900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	medium 18°
Color:	Grey - 16
Weight:	1.85 kg
Size:	A: Ø 110mm B: 251mm C: 135mm



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Waterproof grommet for single cable entry.
- Die-cast aluminium base plate (EN 47100).

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.



DUEDIECI

duedieci



Arcluce Code **0684010A-830-16**
Ex Code **W8850-16 CEI**
Code EAN **8054378208867**



Specifications

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-5.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 90lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Waterproof grommet for single cable entry. Die-cast aluminium base plate (EN 47100).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".


Brand ARCLUCE mod. DUEDIECI

DUEDIECI

duedieci




Arcluce Code **0684011A-830-16**
 Ex Code **W8852-16 CEI**
 Code EAN **8054378208904**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	88lm/W
Luminaire:	21W , 1850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 36°
Color:	Grey - 16
Weight:	1.85 kg
Size:	A: Ø 110mm B: 251mm C: 135mm



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Waterproof grommet for single cable entry.
- Die-cast aluminium base plate (EN 47100).

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.



DUEDIECI

duedieci



Arcluce Code **0684011A-830-16**
Ex Code **W8852-16 CEI**
Code EAN **8054378208904**



Specifications

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-5.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 88lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Waterproof grommet for single cable entry. Die-cast aluminium base plate (EN 47100).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. DUEDIECI

DUEDIECI

duedieci



Arcluce Code **0684014A-830-16**

Ex Code

Code EAN **8054378329524**



Technical information

Light source: LED, 3000K, CRI>80

Luminaire efficacy: 75lm/W

Luminaire: 10W , 750lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz


Wiring: ON/OFF

Optics: narrow 11°

Color: Grey - 16

Weight: 1.85 kg

Size: A: Ø 110mm
B: 251mm
C: 135mm



CE

IP66

IK09

⊕

0,04m²

Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Waterproof grommet for single cable entry.
- Die-cast aluminium base plate (EN 47100).

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

DUEDIECI

duedieci



Arcluce Code **0684014A-830-16**

Ex Code

Code EAN **8054378329524**



Specifications

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-5.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 75lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Waterproof grommet for single cable entry. Die-cast aluminium base plate (EN 47100).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. DUEDIECI