


INTIS

suspended



Arcluce Code **0258020A-840-21**
 Ex Code **L5837-21 CEI**
 Code EAN **8054378199165**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	35W , 3500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 11°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258020A-840-21**
Ex Code **L5837-21 CEI**
Code EAN **8054378199165**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258021A-840-21**
 Ex Code **L5847-21 CEI**
 Code EAN **8054378199400**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	90lm/W
Luminaire:	35W , 3150lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 38°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258021A-840-21**
Ex Code **L5847-21 CEI**
Code EAN **8054378199400**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 90lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258022A-840-21**
 Ex Code **L5857-21 CEI**
 Code EAN **8054378199646**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	81lm/W
Luminaire:	35W , 2850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	very wide flood 65°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258022A-840-21**
Ex Code **L5857-21 CEI**
Code EAN **8054378199646**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 81lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258023A-840-21**
 Ex Code **L5834-21 CEI**
 Code EAN **8054378199080**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	107lm/W
Luminaire:	27W , 2900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 11°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258023A-840-21**
Ex Code **L5834-21 CEI**
Code EAN **8054378199080**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 107lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258024A-840-21**
 Ex Code **L5844-21 CEI**
 Code EAN **8054378199325**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	96lm/W
Luminaire:	27W , 2600lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 38°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258024A-840-21**
Ex Code **L5844-21 CEI**
Code EAN **8054378199325**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 96lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258025A-840-21**
 Ex Code **L5854-21 CEI**
 Code EAN **8054378199561**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	85lm/W
Luminaire:	27W, 2300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	very wide flood 65°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258025A-840-21**
Ex Code **L5854-21 CEI**
Code EAN **8054378199561**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 85lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258026A-840-21**
 Ex Code **L5831-21 CEI**
 Code EAN **8054378199004**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	20W , 2100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 11°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258026A-840-21**
Ex Code **L5831-21 CEI**
Code EAN **8054378199004**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 105lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258027A-840-21**
 Ex Code **L5841-21 CEI**
 Code EAN **8054378199240**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	98lm/W
Luminaire:	20W , 1950lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 38°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258027A-840-21**
Ex Code **L5841-21 CEI**
Code EAN **8054378199240**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 98lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. INTIS

INTIS

suspended



Arcluce Code **0258028A-840-21**
 Ex Code **L5851-21 CEI**
 Code EAN **8054378199486**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	93lm/W
Luminaire:	20W , 1850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	very wide flood 65°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258028A-840-21**
Ex Code **L5851-21 CEI**
Code EAN **8054378199486**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 93lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. INTIS

INTIS


suspended



Arcluce Code **0258034A-840-21**

Ex Code

Code EAN **8054378379246**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	107lm/W
Luminaire:	76W , 8100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	medium 16°
Color:	Aluminium - 21
Weight:	4.2 kg
Size:	A: Ø 211mm B: 220mm

CE

IP66

IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258034A-840-21**

Ex Code

Code EAN **8054378379246**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 107lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. INTIS

INTIS


suspended



Arcluce Code **0258035A-840-21**

Ex Code

Code EAN **8054378379406**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 95lm/W

Luminaire: 76W , 7200lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: flood 40°

Color: Aluminium - 21

Weight: 4.2 kg

Size: A: Ø 211mm
B: 220mm

CE

IP66



IK08



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258035A-840-21**

Ex Code

Code EAN **8054378379406**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 95lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. INTIS

INTIS


suspended



Arcluce Code **0258036A-840-21**

Ex Code

Code EAN **8054378379567**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 90lm/W

Luminaire: 76W , 6850lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: very wide flood 65°

Color: Aluminium - 21

Weight: 4.2 kg

Size: A: Ø 211mm
B: 220mm

CE

IP66



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Ceiling installation.
- Remote control gear box for emergency version 3h.
- Tecnopolymer M20 cable gland.
- Available double cable gland version for through wiring on request.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

INTIS

suspended



Arcluce Code **0258036A-840-21**

Ex Code

Code EAN **8054378379567**



Specifications

INTIS is the ceiling-mounted high-bay luminaire for both indoor and outdoor lighting, featuring a modern and compact design. This high-bay luminaire was specifically created to fit architectures requiring a powerful but discreet illumination.

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 90lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Ceiling installation. Remote control gear box for emergency version 3h. Tecnopolymer M20 cable gland.

Available double cable gland version for through wiring on request.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. INTIS