


JUNO

suspended





Arcluce Code **0237001A-830-24**
 Ex Code **C3784-24 CEI**
 Code EAN **8054378124976**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	75lm/W
Luminaire:	10W , 750lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	medium 22°
Color:	Glossy white - 24
Weight:	1.3 kg
Size:	A: Ø 142mm B: 156mm



Appliance

- Die-cast aluminium body and trim.
- Die-cast aluminium cable cup.
- Polyester powder paint resistant to UV rays.
- Reflector made of anodized aluminium with non-iridescent specular finishing.

Installation

- Suspended installation.
- Suspension with 1.5m transparent cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

JUNO

suspended



Arcluce Code **0237001A-830-24**
Ex Code **C3784-24 CEI**
Code EAN **8054378124976**



Specifications

This stylish pendant luminaire for indoor lighting, also available for electrified track installation, represents a real design detail able to enhance interiors with its elegance and its high visual comfort lighting. Recommended for both functional and decorative lighting, it perfectly integrates into different environments thanks to its range of colours: classical black, refined green or delicate white.

Die-cast aluminium body and trim. Die-cast aluminium cable cup. Polyester powder paint resistant to UV rays. Reflector made of anodized aluminium with non-iridescent specular finishing.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 75lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Suspended installation. Suspension with 1.5m transparent cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".


Brand ARCLUCE mod. JUNO

JUNO

suspended





Arcluce Code **0237003A-830-24**
 Ex Code **C3786-24 CEI**
 Code EAN **8054378125058**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	10W , 1000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 46°
Color:	Glossy white - 24
Weight:	1.3 kg
Size:	A: Ø 142mm B: 156mm



Appliance

- Die-cast aluminium body and trim.
- Die-cast aluminium cable cup.
- Polyester powder paint resistant to UV rays.
- Reflector made of anodized aluminium with non-iridescent specular finishing.

Installation

- Suspended installation.
- Suspension with 1.5m transparent cable.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

JUNO

suspended



Arcluce Code **0237003A-830-24**
Ex Code **C3786-24 CEI**
Code EAN **8054378125058**



Specifications

This stylish pendant luminaire for indoor lighting, also available for electrified track installation, represents a real design detail able to enhance interiors with its elegance and its high visual comfort lighting. Recommended for both functional and decorative lighting, it perfectly integrates into different environments thanks to its range of colours: classical black, refined green or delicate white.

Die-cast aluminium body and trim. Die-cast aluminium cable cup. Polyester powder paint resistant to UV rays. Reflector made of anodized aluminium with non-iridescent specular finishing.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Suspended installation. Suspension with 1.5m transparent cable.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. JUNO