


KRION

performance



Arcluce Code **0485018A-840-21**
 Ex Code **P8521-21 CEI**
 Code EAN **8054378204364**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	15W , 1500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 12°
Color:	Aluminium - 21
Weight:	2.1 kg
Size:	A: 108mm B: 88mm C: 346mm

CE

IP66

IK08



0,03m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485018A-840-21**
Ex Code **P8521-21 CEI**
Code EAN **8054378204364**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485019A-840-21**
 Ex Code **P8524-21 CEI**
 Code EAN **8054378204401**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	109lm/W
Luminaire:	28W , 3050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 12°
Color:	Aluminium - 21
Weight:	3.3 kg
Size:	A: 108mm B: 88mm C: 639mm

CE

IP66

IK08



0,06m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485019A-840-21**
Ex Code **P8524-21 CEI**
Code EAN **8054378204401**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 109lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485020A-840-21**
 Ex Code **P8527-21 CEI**
 Code EAN **8054378204449**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	111lm/W
Luminaire:	56W , 6200lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 12°
Color:	Aluminium - 21
Weight:	6.3 kg
Size:	A: 108mm B: 88mm C: 1225mm

CE

IP66

IK08



0,11m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485020A-840-21**
Ex Code **P8527-21 CEI**
Code EAN **8054378204449**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 111lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485021A-840-21**
 Ex Code **P8531-21 CEI**
 Code EAN **8054378204487**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	15W , 1500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
Color:	Aluminium - 21
Weight:	2.1 kg
Size:	A: 108mm B: 88mm C: 346mm

CE

IP66

IK08

⊕

0,03m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485021A-840-21**
Ex Code **P8531-21 CEI**
Code EAN **8054378204487**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485022A-840-21**
 Ex Code **P8534-21 CEI**
 Code EAN **8054378204524**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	109lm/W
Luminaire:	28W , 3050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
Color:	Aluminium - 21
Weight:	3.3 kg
Size:	A: 108mm B: 88mm C: 639mm

CE

IP66

IK08



0,06m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485022A-840-21**
Ex Code **P8534-21 CEI**
Code EAN **8054378204524**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 109lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance





Arcluce Code **0485023A-840-21**
 Ex Code **P8537-21 CEI**
 Code EAN **8054378204562**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	111lm/W
Luminaire:	56W , 6200lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
Color:	Aluminium - 21
Weight:	6.3 kg
Size:	A: 108mm B: 88mm C: 1225mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485023A-840-21**
Ex Code **P8537-21 CEI**
Code EAN **8054378204562**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 111lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance





Arcluce Code **0485024A-840-21**
 Ex Code **P8541-21 CEI**
 Code EAN **8054378204609**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	90lm/W
Luminaire:	15W , 1350lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 47°
Color:	Aluminium - 21
Weight:	2.1 kg
Size:	A: 108mm B: 88mm C: 346mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485024A-840-21**
Ex Code **P8541-21 CEI**
Code EAN **8054378204609**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 90lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance






Arcluce Code **0485025A-840-21**
 Ex Code **P8544-21 CEI**
 Code EAN **8054378204647**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	96lm/W
Luminaire:	28W , 2700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 47°
Color:	Aluminium - 21
Weight:	3.3 kg
Size:	A: 108mm B: 88mm C: 639mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485025A-840-21**
Ex Code **P8544-21 CEI**
Code EAN **8054378204647**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 96lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485026A-840-21**
 Ex Code **P8547-21 CEI**
 Code EAN **8054378204685**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	98lm/W
Luminaire:	56W , 5500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 47°
Color:	Aluminium - 21
Weight:	6.3 kg
Size:	A: 108mm B: 88mm C: 1225mm

CE

IP66

IK08



0,11m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485026A-840-21**
Ex Code **P8547-21 CEI**
Code EAN **8054378204685**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 98lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485027A-840-21**
 Ex Code **P8551-21 CEI**
 Code EAN **8054378204722**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	93lm/W
Luminaire:	15W , 1400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	elliptic 10°x55°
Color:	Aluminium - 21
Weight:	2.1 kg
Size:	A: 108mm B: 88mm C: 346mm

CE

IP66

IK08



0,03m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485027A-840-21**
Ex Code **P8551-21 CEI**
Code EAN **8054378204722**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 93lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485028A-840-21**
 Ex Code **P8554-21 CEI**
 Code EAN **8054378204760**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	28W , 2800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	elliptic 10°x55°
Color:	Aluminium - 21
Weight:	3.3 kg
Size:	A: 108mm B: 88mm C: 639mm

CE

IP66

IK08



0,06m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485028A-840-21**
Ex Code **P8554-21 CEI**
Code EAN **8054378204760**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 100lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485029A-840-21**
 Ex Code **P8557-21 CEI**
 Code EAN **8054378204807**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	102lm/W
Luminaire:	56W , 5700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	elliptic 10°x55°
Color:	Aluminium - 21
Weight:	6.3 kg
Size:	A: 108mm B: 88mm C: 1225mm

CE

IP66

IK08



0,11m²

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485029A-840-21**
Ex Code **P8557-21 CEI**
Code EAN **8054378204807**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 102lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance






Arcluce Code **0485030A-840-21**
 Ex Code **P8561-21 CEI**
 Code EAN **8054378204845**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	97lm/W
Luminaire:	15W , 1450lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wall washer lmax=18°
Color:	Aluminium - 21
Weight:	2.1 kg
Size:	A: 108mm B: 88mm C: 346mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485030A-840-21**
Ex Code **P8561-21 CEI**
Code EAN **8054378204845**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 97lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance



Arcluce Code **0485031A-840-21**
 Ex Code **P8564-21 CEI**
 Code EAN **8054378204883**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	28W , 2950lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wall washer lmax=18°
Color:	Aluminium - 21
Weight:	3.3 kg
Size:	A: 108mm B: 88mm C: 639mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485031A-840-21**
Ex Code **P8564-21 CEI**
Code EAN **8054378204883**



Specifications


Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 105lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION

KRION

performance





Arcluce Code **0485032A-840-21**
 Ex Code **P8567-21 CEI**
 Code EAN **8054378204920**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	106lm/W
Luminaire:	56W , 5950lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wall washer lmax=18°
Color:	Aluminium - 21
Weight:	6.3 kg
Size:	A: 108mm B: 88mm C: 1225mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- SUPPORT BRACKETS TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

KRION

performance



Arcluce Code **0485032A-840-21**
Ex Code **P8567-21 CEI**
Code EAN **8054378204920**



Specifications

Extruded aluminium body. Die-cast aluminium caps (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. Goniometer scale to aim light. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-5. LED sources available in color temperatures 4000K High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C). System effectiveness, minimum 106lm/W Luminaire in insulation class I. DRIVER INCLUDED. Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring. These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light". Brand ARCLUCE mod. KRION