



LUNIO

performance

Arcluce Code **0875002A-840-21**
 Ex Code **S7511-21 CEI**
 Code EAN **8054378206603**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	98lm/W
Luminaire:	30W , 2950lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type IV
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm

CE

IP66

IK09



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.

LUNIO

performance

Arcluce Code **0875002A-840-21**
Ex Code **S7511-21 CEI**
Code EAN **8054378206603**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 98lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875006A-840-21**
 Ex Code **S7513-21 CEI**
 Code EAN **8054378206665**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	94lm/W
Luminaire:	43W , 4050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type IV
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm

CE

IP66

IK09



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.

LUNIO

performance

Arcluce Code **0875006A-840-21**
Ex Code **S7513-21 CEI**
Code EAN **8054378206665**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 94lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875010A-840-21**
 Ex Code **S7501-21 CEI**
 Code EAN **8054378206429**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	41W , 4300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type V
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm



IP66



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.

LUNIO

performance

Arcluce Code **0875010A-840-21**
Ex Code **S7501-21 CEI**
Code EAN **8054378206429**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 105lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875014A-840-21**
 Ex Code **S7515-21 CEI**
 Code EAN **8054378206726**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	57W , 5700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type IV
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm



IP66



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



LUNIO

performance

Arcluce Code **0875014A-840-21**
Ex Code **S7515-21 CEI**
Code EAN **8054378206726**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875018A-840-21**
 Ex Code **S7503-21 CEI**
 Code EAN **8054378206481**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	106lm/W
Luminaire:	57W , 6050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type V
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm

CE

IP66

IK09



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.

LUNIO

performance

Arcluce Code **0875018A-840-21**
Ex Code **S7503-21 CEI**
Code EAN **8054378206481**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 106lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875022A-840-21**
 Ex Code **S7505-21 CEI**
 Code EAN **8054378206542**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	80W , 8400lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type V
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm



IP66



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.



LUNIO

performance

Arcluce Code **0875022A-840-21**
Ex Code **S7505-21 CEI**
Code EAN **8054378206542**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 105lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875029A-840-21**
 Ex Code
 Code EAN **8054378406430**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	86lm/W
Luminaire:	80W , 6900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type IV
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm

CE

IP66

IK09



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO

performance

Arcluce Code **0875029A-840-21**

Ex Code

Code EAN **8054378406430**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 86lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO

LUNIO

performance

Arcluce Code **0875030A-840-21**
 Ex Code
 Code EAN **8054378406614**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	92lm/W
Luminaire:	110W , 10150lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type V
Color:	Aluminium - 21
Weight:	9 kg
Size:	A: Ø 520mm B: 377mm

CE

IP66

IK09



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 5mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.

LUNIO

performance

Arcluce Code **0875030A-840-21**
Ex Code
Code EAN **8054378406614**



Specifications

Unique design for urban lighting. Catchy shape, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: LUNIO is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 92lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO