

Urban lighting

## **LUNIO7**



### LUMINAIRE

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges up to 4kV.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-3.

### INSTALLATION

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

**Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.**

STANDARD PRODUCT		AVAILABLE OPTIONS	
Wiring	ON/OFF (A)	DALI (B), BIP (E)	
CCT	4000K (-840)	3000K (-830)	
Colour	<input type="radio"/> 21	<input checked="" type="radio"/> 12, <input type="radio"/> 16	



📍 Aura Town Centre - Queensland's Sunshine Coast, Australia

Urban lighting



# LUNIO7











STANDARD COLOUR

 21

DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0876007A-840-21	 type II	35W	3600lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-
0876011A-840-21	 type II	69W	7300lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-
0876013A-840-21	 type III	35W	3900lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-
0876017A-840-21	 type III	69W	8000lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-
0876003A-840-21	 type IV	35W	3600lm	80	4000K	□	ON/OFF	220-240V/50-60Hz	520	627	-
0876004A-840-21	 type IV	69W	7200lm	80	4000K	□	ON/OFF	220-240V/50-60Hz	520	627	-
0876001A-840-21	 type VS-W	35W	3300lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-
0876005A-840-21	 type VS-W	69W	6500lm	80	4000K	□	ON/OFF	220-240V 50/60Hz	520	627	-

The **photo** represents the family product range. You can see the correct image of each product (code) on the website.



For post top mounting, check all available solutions on page 402.

**LED driver included.**


**Available on request:**  
versions with Future-Proof





📍 Aura Town Centre - Queensland's Sunshine Coast, Australia

