



LUNIO7

lunio7

Arcluce Code **0876001A-840-21**

Ex Code

Code EAN **8054378337703**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 94lm/W

Luminaire: 35W , 3300lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type VS-W

Color: Aluminium - 21

Weight: 12.6 kg

Size: A: Ø 520mm
B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO7

lunio7

Arcluce Code **0876001A-840-21**

Ex Code

Code EAN **8054378337703**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 94lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876003A-840-21**

Ex Code

Code EAN **8054378406799**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	35W , 3600lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V/50-60Hz
Wiring:	ON/OFF
Optics:	type IV
Color:	Aluminium - 21
Weight:	12.6 kg
Size:	A: Ø 520mm B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO7

lunio7

Arcluce Code **0876003A-840-21**

Ex Code

Code EAN **8054378406799**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876004A-840-21**

Ex Code

Code EAN **8054378406973**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 104lm/W

Luminaire: 69W , 7200lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V/50-60Hz

Wiring: ON/OFF

Optics: type IV

Color: Aluminium - 21

Weight: 12.6 kg

Size: A: Ø 520mm
B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO7

lunio7

Arcluce Code **0876004A-840-21**

Ex Code

Code EAN **8054378406973**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 104lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876005A-840-21**

Ex Code

Code EAN **8054378337888**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	94lm/W
Luminaire:	69W , 6500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS-W
Color:	Aluminium - 21
Weight:	12.6 kg
Size:	A: Ø 520mm B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




LUNIO7

lunio7

Arcluce Code **0876005A-840-21**

Ex Code

Code EAN **8054378337888**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 94lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876007A-840-21**

Ex Code

Code EAN **8054378338069**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 103lm/W

Luminaire: 35W , 3600lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: type II

Color: Aluminium - 21

Weight: 12.6 kg

Size: A: Ø 520mm
B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




LUNIO7

lunio7

Arcluce Code **0876007A-840-21**

Ex Code

Code EAN **8054378338069**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876011A-840-21**

Ex Code

Code EAN **8054378338243**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	106lm/W
Luminaire:	69W , 7300lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type II
Color:	Aluminium - 21
Weight:	12.6 kg
Size:	A: Ø 520mm B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO7

lunio7

Arcluce Code **0876011A-840-21**

Ex Code

Code EAN **8054378338243**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 106lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876013A-840-21**

Ex Code

Code EAN **8054378338427**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	111lm/W
Luminaire:	35W , 3900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type III
Color:	Aluminium - 21
Weight:	12.6 kg
Size:	A: Ø 520mm B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


LUNIO7

lunio7

Arcluce Code **0876013A-840-21**

Ex Code

Code EAN **8054378338427**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 111lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7



LUNIO7

lunio7

Arcluce Code **0876017A-840-21**

Ex Code

Code EAN **8054378338601**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	116lm/W
Luminaire:	69W , 8000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type III
Color:	Aluminium - 21
Weight:	12.6 kg
Size:	A: Ø 520mm B: 627mm

CE

IP66

IK08



0,16m²



Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




LUNIO7

lunio7

Arcluce Code **0876017A-840-21**

Ex Code

Code EAN **8054378338601**



Specifications

Urban lighting with a stylish touch LUNIO7 is the pole-top luminaire which adds a touch of modern elegance to urban lighting, with the highest quality of light typical of Arcluce solutions. Its high performance optics generate a directed light, managed by the bi-power system to optimize intensity and consumptions, without producing light pollution. It can be equipped with the latest technologies for smart lighting.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 116lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. LUNIO7