



# MIKO Grande

performance

Arcluce Code **0886000A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	117lm/W
<b>Luminaire:</b>	30W , 3500lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886000A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886001A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	123lm/W
<b>Luminaire:</b>	48W , 5900lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886001A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 123lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886002A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	113lm/W
<b>Luminaire:</b>	30W , 3400lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type II
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886002A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 113lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886003A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	110lm/W
<b>Luminaire:</b>	48W , 5300lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type II
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886003A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 110lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. MIKO Grande





# MIKO Grande

performance

Arcluce Code **0886004A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	120lm/W
<b>Luminaire:</b>	30W , 3600lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type III
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886004A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 120lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886005A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	117lm/W
<b>Luminaire:</b>	48W , 5600lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type III
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886005A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886006A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	123lm/W
<b>Luminaire:</b>	30W , 3700lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type IV
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886006A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 123lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886007A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	119lm/W
<b>Luminaire:</b>	48W , 5700lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type IV
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886007A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 119lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. MIKO Grande





# MIKO Grande

performance

Arcluce Code **0886008A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	120lm/W
<b>Luminaire:</b>	30W , 3600lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type IV-L
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886008A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 120lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.



Brand ARCLUCE mod. MIKO Grande

# MIKO Grande

performance

Arcluce Code **0886009A-840-21**

Ex Code



## Technical information

<b>Light source:</b>	LED, 4000K
<b>Luminaire efficacy:</b>	117lm/W
<b>Luminaire:</b>	48W , 5600lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type IV-L
<b>Color:</b>	Aluminium - 21
<b>Weight:</b>	4.3 kg
<b>Size:</b>	A: Ø 360mm B: 305mm

CE

IP66

IK09



0,04m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Post-top installation (Ø60mm or Ø76mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-3.

# MIKO Grande

performance

Arcluce Code **0886009A-840-21**

Ex Code



## Specifications

Essential design for urban lighting. Clean and functional lines, high performance optics, provided with the latest technologies for smart lighting and energy efficiency: MIKO Grande is the pole top luminaire for urban lighting which combines elegance and innovation with the highest quality of light, without producing light pollution.

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm or Ø76mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. MIKO Grande