



MIKO Bollard

radial

Arcluce Code **0872000A-830-21**
 Ex Code **S7700-21 CEI**
 Code EAN **8054378207464**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	85lm/W
Luminaire:	20W , 1700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Aluminium - 21
Weight:	2.05 kg
Size:	A: Ø 200mm B: 76mm C: 300mm

CE

IP66

IK08



0,03m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

radial

Arcluce Code **0872000A-830-21**
Ex Code **S7700-21 CEI**
Code EAN **8054378207464**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 85lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard

MIKO Bollard

radial

Arcluce Code **0872001A-830-21**
 Ex Code **S7702-21 CEI**
 Code EAN **8054378207501**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	85lm/W
Luminaire:	20W , 1700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Aluminium - 21
Weight:	2.65 kg
Size:	A: Ø 200mm B: 76mm C: 600mm

CE

IP66

IK08



0,05m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

radial

Arcluce Code **0872001A-830-21**
Ex Code **S7702-21 CEI**
Code EAN **8054378207501**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 85lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard

MIKO Bollard

radial

Arcluce Code **0872002A-830-21**
 Ex Code **S7704-21 CEI**
 Code EAN **8054378207549**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	85lm/W
Luminaire:	20W , 1700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Aluminium - 21
Weight:	3.05 kg
Size:	A: Ø 200mm B: 76mm C: 800mm

CE

IP66

IK08



0,06m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.


Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

radial

Arcluce Code **0872002A-830-21**
Ex Code **S7704-21 CEI**
Code EAN **8054378207549**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 85lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard

MIKO Bollard

radial

Arcluce Code **0872003A-830-21**
 Ex Code **S7706-21 CEI**
 Code EAN **8054378207587**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	85lm/W
Luminaire:	20W , 1700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	radial
Color:	Aluminium - 21
Weight:	3.45 kg
Size:	A: Ø 200mm B: 76mm C: 1000mm

CE

IP66

IK08



0,08m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.

Norm


- It complies with standards EN 60598-1 and EN 60598-2-1.



MIKO Bollard

radial

Arcluce Code **0872003A-830-21**
Ex Code **S7706-21 CEI**
Code EAN **8054378207587**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 85lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard


MIKO Bollard

oneway

Arcluce Code **0872004A-830-21**

Ex Code

Code EAN **8054378405716**



Technical information

Light source: LED, 3000K, CRI>80

Luminaire efficacy: 80lm/W

Luminaire: 10W , 800lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: one way

Color: Aluminium - 21

Weight: 2.05 kg

Size:
A: Ø 200mm
B: 76mm
C: 300mm

CE

IP66

IK08



0,03m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

oneway

Arcluce Code **0872004A-830-21**

Ex Code

Code EAN **8054378405716**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 80lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard


MIKO Bollard

oneway

Arcluce Code **0872005A-830-21**

Ex Code

Code EAN **8054378405792**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	80lm/W
Luminaire:	10W , 800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Aluminium - 21
Weight:	2.65 kg
Size:	A: Ø 200mm B: 76mm C: 600mm

CE

IP66

IK08



0,05m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

oneway

Arcluce Code **0872005A-830-21**

Ex Code

Code EAN **8054378405792**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 80lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard


MIKO Bollard

oneway

Arcluce Code **0872006A-830-21**

Ex Code

Code EAN **8054378405877**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	80lm/W
Luminaire:	10W , 800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Aluminium - 21
Weight:	3.05 kg
Size:	A: Ø 200mm B: 76mm C: 800mm

CE

IP66

IK08



0,06m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

oneway

Arcluce Code **0872006A-830-21**

Ex Code

Code EAN **8054378405877**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 80lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard


MIKO Bollard

oneway

Arcluce Code **0872007A-830-21**

Ex Code

Code EAN **8054378405952**



Technical information

Light source:	LED, 3000K, CRI>80
Luminaire efficacy:	80lm/W
Luminaire:	10W , 800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	one way
Color:	Aluminium - 21
Weight:	3.45 kg
Size:	A: Ø 200mm B: 76mm C: 1000mm

CE

IP66

IK08



0,08m²

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 4mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Bollard installation.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.
- ALSO AVAILABLE IN WALL VERSION.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

MIKO Bollard

oneway

Arcluce Code **0872007A-830-21**

Ex Code

Code EAN **8054378405952**



Specifications

The sophisticated bollard light for outdoor private and public lighting
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 80lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Bollard installation. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. MIKO Bollard