



# QUADRIO180





comfort

Arcluce Code      **0868002A-840-16**  
 Ex Code            **S7180-16 CEI**  
 Code EAN          **8054378096648**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	57lm/W
<b>Luminaire:</b>	45W , 2550lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	33.5 kg
<b>Size:</b>	A: 180mm B: 3435mm C: 1121mm



## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation

- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.



## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

# QUADRIO180

comfort

Arcluce Code           **0868002A-840-16**  
Ex Code               **S7180-16 CEI**  
Code EAN              **8054378096648**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 57lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180

# QUADRIO180




comfort

Arcluce Code      **0868003A-840-16**  
 Ex Code            **S7181-16 CEI**  
 Code EAN          **8054378096662**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	57lm/W
<b>Luminaire:</b>	45W , 2550lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	38.5 kg
<b>Size:</b>	A: 180mm B: 3935mm C: 1121mm



## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation

- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.


## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

# QUADRIO180

comfort

Arcluce Code           **0868003A-840-16**  
Ex Code               **S7181-16 CEI**  
Code EAN              **8054378096662**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 57lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).



These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180

# QUADRIO180

comfort

Arcluce Code **0868004A-840-16**  
 Ex Code **S7185-16 CEI**  
 Code EAN **8054378158841**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	57lm/W
<b>Luminaire:</b>	45W , 2550lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	43.5 kg
<b>Size:</b>	A: 180mm B: 4435mm C: 1621mm

CE

IP66

IK07



0,80m<sup>2</sup>

850°

## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation


- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm


- It complies with standards EN 60598-1 and EN 60598-2-1.



# QUADRIO180

comfort

Arcluce Code           **0868004A-840-16**  
Ex Code               **S7185-16 CEI**  
Code EAN              **8054378158841**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 57lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180



# QUADRIO180

performance

Arcluce Code **0868005A-840-16**



Ex Code

Code EAN **8054378334498**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	64lm/W
<b>Luminaire:</b>	37W , 2350lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	36.5 kg
<b>Size:</b>	A: 180mm B: 3435mm C: 1121mm



## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation

- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.


# QUADRIO180

performance

Arcluce Code **0868005A-840-16**

Ex Code

Code EAN **8054378334498**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 64lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180





# QUADRIO180

performance

Arcluce Code **0868006A-840-16**

Ex Code

Code EAN **8054378334610**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	64lm/W
<b>Luminaire:</b>	37W , 2350lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	38.5 kg
<b>Size:</b>	A: 180mm B: 3935mm C: 1621mm

CE

IP66

IK07



0,70m<sup>2</sup>

## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation

- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.


# QUADRIO180

performance

Arcluce Code **0868006A-840-16**

Ex Code

Code EAN **8054378334610**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 64lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180



# QUADRIO180

performance

Arcluce Code **0868007A-840-16**

Ex Code

Code EAN **8054378334733**



## Technical information

<b>Light source:</b>	LED, 4000K, CRI>80
<b>Luminaire efficacy:</b>	64lm/W
<b>Luminaire:</b>	37W , 2350lm
<b>LED life time:</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	type VS
<b>Color:</b>	Grey - 16
<b>Weight:</b>	43.5 kg
<b>Size:</b>	A: 180mm B: 4435mm C: 1621mm

CE

IP66

IK07



0,80m<sup>2</sup>

## Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- Driver protected against voltage surges.
- PMMA lenses for LEDs.
- Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

## Installation


- At ground installation.
- Zinc-coated steel basement for ground anchoring for rawplugs.
- Supplied with power cable.
- Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".
- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.




# QUADRIO180

performance

Arcluce Code **0868007A-840-16**

Ex Code

Code EAN **8054378334733**



## Specifications

The LED fitting in bollard and urban version for garden and urban lighting  
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen in opal PMMA stabilized against UV rays or in 5 mm thick tempered glass resistant to thermal shocks.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 64lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

At ground installation. Zinc-coated steel basement for ground anchoring for rawplugs. Supplied with power cable. Supplied complete with inspection slit with junction box and fuse terminal block (6.3A fuse, 5x20mm, included).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. QUADRIO180