

High protection degree recessed luminaires

## **RAY**LINEA



### LUMINAIRE

- Extruded aluminium body.
- Die-cast aluminium end caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-2.


### INSTALLATION

- Recessed installation.
- Double cable gland M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

STANDARD PRODUCT		AVAILABLE OPTIONS	
Wiring	ON/OFF (A)	DALI (B) - ON/OFF-E (G) - DALI-E (H)	
CCT	4000K (-840)	3000K (-830)	
Colour	<input type="radio"/> 11	<input type="radio"/> 21	



 Millefiori MILANO Shop, Milano, Italy

High protection degree recessed luminaires


# RAYLINEA



STANDARD COLOUR



DIMENSIONS



Code	Optic	Luminaire		CRI	CCT	Class	Wiring	Power Supply	A mm	B mm	C mm
		Watt	Lumen								
0373004A-840-11	narrow 11°	20W	2100lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373013A-840-11	narrow 11°	40W	4200lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246
0373003A-840-11	flood 26°	20W	2000lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373012A-840-11	flood 26°	40W	4000lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246
0373005A-840-11	wide flood 46°	20W	1850lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373014A-840-11	wide flood 46°	40W	3700lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246
0373001A-840-11	extra wide flood 135°x140°	20W	1250lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373010A-840-11	extra wide flood 135°x140°	40W	2500lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246
0373002A-840-11	elliptic 9°x47°	20W	1900lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373011A-840-11	elliptic 9°x47°	40W	3800lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246
0373006A-840-11	wall washer lmax=20°	20W	2050lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	646
0373015A-840-11	wall washer lmax=20°	40W	4100lm	80	4000K	⊕	ON/OFF	220-240V 50/60Hz	100	97	1246

The photo represents the family product range. You can see the correct image of each product (code) on the website.

## ACCESSORIES



Code	Kg
1099409X	0,03

IP68 linear joint -  
2 ways - 3 poles.



Fixtures suitable for installation on plasterboard, wood or metal ceilings of thickness ranging between 1mm and 20mm.

LED driver included.



📍 MAXIMA Shopping/Office Center - Vilnius, Lithuania