


RAY-LINEA

RAY-LINEA



Arcluce Code **0373001A-840-11**
 Ex Code **H7381-11 CEI**
 Code EAN **8054378149764**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	63lm/W
Luminaire:	20W , 1250lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	extra wide flood 135°x140°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm

CE

IP67

IK10



85x640mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373001A-840-11**
Ex Code **H7381-11 CEI**
Code EAN **8054378149764**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 63lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373002A-840-11**
 Ex Code **H7341-11 CEI**
 Code EAN **8054378097751**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	95lm/W
Luminaire:	20W , 1900lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	elliptic 9°x47°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm

CE

IP67

IK10



85x640mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373002A-840-11**
Ex Code **H7341-11 CEI**
Code EAN **8054378097751**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 95lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373003A-840-11**
 Ex Code **H7351-11 CEI**
 Code EAN **8054378008115**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	20W , 2000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373003A-840-11**
Ex Code **H7351-11 CEI**
Code EAN **8054378008115**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373004A-840-11**
 Ex Code **H7331-11 CEI**
 Code EAN **8054378097539**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	20W , 2100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 11°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373004A-840-11**
Ex Code **H7331-11 CEI**
Code EAN **8054378097539**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 105lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373005A-840-11**
 Ex Code **H7361-11 CEI**
 Code EAN **8054378148569**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	93lm/W
Luminaire:	20W , 1850lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 46°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373005A-840-11**
Ex Code **H7361-11 CEI**
Code EAN **8054378148569**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 93lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373006A-840-11**
 Ex Code **H7371-11 CEI**
 Code EAN **8054378149160**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	20W , 2050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wall washer lmax=20°
Color:	White - 11
Weight:	3.2 kg
Recessed hole:	85x640mm
Size:	A: 100mm B: 97mm C: 646mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373006A-840-11**
Ex Code **H7371-11 CEI**
Code EAN **8054378149160**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373010A-840-11**
 Ex Code **H7384-11 CEI**
 Code EAN **8054378150043**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	63lm/W
Luminaire:	40W , 2500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	extra wide flood 135°x140°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm

CE

IP67

IK10



85x1240mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373010A-840-11**
Ex Code **H7384-11 CEI**
Code EAN **8054378150043**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 63lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373011A-840-11**
 Ex Code **H7344-11 CEI**
 Code EAN **8054378097836**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	95lm/W
Luminaire:	40W , 3800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	elliptic 9°x47°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm

CE

IP67

IK10



85x1240mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373011A-840-11**
Ex Code **H7344-11 CEI**
Code EAN **8054378097836**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 95lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373012A-840-11**
 Ex Code **H7354-11 CEI**
 Code EAN **8033765673556**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	40W , 4000lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 26°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm

CE

IP67

IK10



85x1240mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373012A-840-11**
Ex Code **H7354-11 CEI**
Code EAN **8033765673556**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA




Arcluce Code **0373013A-840-11**
 Ex Code **H7334-11 CEI**
 Code EAN **8054378097614**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	105lm/W
Luminaire:	40W , 4200lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	narrow 11°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373013A-840-11**
Ex Code **H7334-11 CEI**
Code EAN **8054378097614**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 105lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373014A-840-11**
 Ex Code **H7364-11 CEI**
 Code EAN **8054378148842**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	93lm/W
Luminaire:	40W , 3700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wide flood 46°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm

CE

IP67

IK10



85x1240mm

Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373014A-840-11**
Ex Code **H7364-11 CEI**
Code EAN **8054378148842**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 93lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.


Brand ARCLUCE mod. RAY-LINEA

RAY-LINEA

RAY-LINEA



Arcluce Code **0373015A-840-11**
 Ex Code **H7374-11 CEI**
 Code EAN **8054378149443**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	103lm/W
Luminaire:	40W , 4100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	wall washer lmax=20°
Color:	White - 11
Weight:	5.8 kg
Recessed hole:	85x1240mm
Size:	A: 100mm B: 97mm C: 1246mm



Appliance

- Extruded aluminium body.
- Die-cast aluminium caps.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double grommet M16 for through wiring.
- Fixing with adjustable stainless steel brackets.
- Supplied with power cable (0.7m).

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.

RAY-LINEA

RAY-LINEA



Arcluce Code **0373015A-840-11**
Ex Code **H7374-11 CEI**
Code EAN **8054378149443**



Specifications

The linear recessed ceiling downlight for suggestive and functional light paths
Extruded aluminium body. Die-cast aluminium caps. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 8mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 103lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Recessed installation. Double grommet M16 for through wiring. Fixing with adjustable stainless steel brackets. Supplied with power cable (0.7m).

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. RAY-LINEA