

STILO


stilo40 - comfort



Arcluce Code **0231002A-930-11**

Ex Code

Code EAN **8054378414367**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	88lm/W
Luminaire:	6W , 525lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 37°
Color:	White - 11
Weight:	1.35 kg
Size:	A: Ø 40mm B: 300mm

CE

IP20



Appliance

- Extruded aluminium body.
- Polyester powder paint resistant to UV rays.
- PMMA opal screen or comfort optic in polycarbonate.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Engineering plastic base plate.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

STILO

stilo40 - comfort



Arcluce Code **0231002A-930-11**

Ex Code

Code EAN **8054378414367**



Specifications

The elegant suspended luminaire for interior lighting This elegant suspended downlight is the perfect lighting solution to add a touch of style to modern interiors: the high quality of light ensures maximum visual comfort, specially in opal screen versions, and the characteristic shape of the luminaire completes and enhances the interior design.

Extruded aluminium body. Polyester powder paint resistant to UV rays. PMMA opal screen or comfort optic in polycarbonate. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 88lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Engineering plastic base plate.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. STILO

STILO


stilo40 - opal



Arcluce Code **0231003A-930-11**

Ex Code

Code EAN **8054378417771**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	92lm/W
Luminaire:	6W , 550lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 36°
Color:	White - 11
Weight:	1.35 kg
Size:	A: Ø 40mm B: 300mm

CE

IP20



Appliance

- Extruded aluminium body.
- Polyester powder paint resistant to UV rays.
- PMMA opal screen or comfort optic in polycarbonate.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Engineering plastic base plate.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

STILO

stilo40 - opal



Arcluce Code **0231003A-930-11**

Ex Code

Code EAN **8054378417771**



Specifications

The elegant suspended luminaire for interior lighting This elegant suspended downlight is the perfect lighting solution to add a touch of style to modern interiors: the high quality of light ensures maximum visual comfort, specially in opal screen versions, and the characteristic shape of the luminaire completes and enhances the interior design.

Extruded aluminium body. Polyester powder paint resistant to UV rays. PMMA opal screen or comfort optic in polycarbonate. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 92lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Engineering plastic base plate.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. STILO

STILO


stilo50 - comfort



Arcluce Code **0231022A-930-11**

Ex Code

Code EAN **8054378414404**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	91lm/W
Luminaire:	8W , 725lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 37°
Color:	White - 11
Weight:	1.65 kg
Size:	A: Ø 50mm B: 300mm

CE

IP20



Appliance

- Extruded aluminium body.
- Polyester powder paint resistant to UV rays.
- PMMA opal screen or comfort optic in polycarbonate.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Engineering plastic base plate.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

STILO

stilo50 - comfort



Arcluce Code **0231022A-930-11**

Ex Code

Code EAN **8054378414404**



Specifications

The elegant suspended luminaire for interior lighting This elegant suspended downlight is the perfect lighting solution to add a touch of style to modern interiors: the high quality of light ensures maximum visual comfort, specially in opal screen versions, and the characteristic shape of the luminaire completes and enhances the interior design.

Extruded aluminium body. Polyester powder paint resistant to UV rays. PMMA opal screen or comfort optic in polycarbonate. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 91lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Engineering plastic base plate.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. STILO

STILO


stilo50 - opal



Arcluce Code **0231023A-930-11**

Ex Code

Code EAN **8054378417795**



Technical information

Light source:	LED, 3000K
Luminaire efficacy:	94lm/W
Luminaire:	8W , 750lm
LED life time:	> 50000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	flood 36°
Color:	White - 11
Weight:	1.65 kg
Size:	A: Ø 50mm B: 300mm

CE

IP20



Appliance

- Extruded aluminium body.
- Polyester powder paint resistant to UV rays.
- PMMA opal screen or comfort optic in polycarbonate.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Engineering plastic base plate.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.

STILO

stilo50 - opal



Arcluce Code **0231023A-930-11**

Ex Code

Code EAN **8054378417795**



Specifications

The elegant suspended luminaire for interior lighting This elegant suspended downlight is the perfect lighting solution to add a touch of style to modern interiors: the high quality of light ensures maximum visual comfort, specially in opal screen versions, and the characteristic shape of the luminaire completes and enhances the interior design.

Extruded aluminium body. Polyester powder paint resistant to UV rays. PMMA opal screen or comfort optic in polycarbonate. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 94lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Engineering plastic base plate.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. STILO