



ZOYA

comfort

Arcluce Code **0879000A-840-21**

Ex Code

Code EAN **8054378339868**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	109lm/W
Luminaire:	40W , 4350lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8.6 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


ZOYA

comfort

Arcluce Code **0879000A-840-21**

Ex Code

Code EAN **8054378339868**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 109lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

comfort

Arcluce Code **0879001A-840-21**

Ex Code

Code EAN **8054378340048**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	104lm/W
Luminaire:	56W , 5800lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8.6 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


ZOYA

comfort

Arcluce Code **0879001A-840-21**

Ex Code

Code EAN **8054378340048**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 104lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

comfort

Arcluce Code **0879002A-840-21**

Ex Code

Code EAN **8054378340222**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	95lm/W
Luminaire:	81W , 7700lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8.6 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




ZOYA

comfort

Arcluce Code **0879002A-840-21**

Ex Code

Code EAN **8054378340222**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 95lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

opal

Arcluce Code **0879003A-840-21**

Ex Code

Code EAN **8054378340406**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	113lm/W
Luminaire:	40W , 4500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


ZOYA

opal

Arcluce Code **0879003A-840-21**

Ex Code

Code EAN **8054378340406**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 113lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

opal

Arcluce Code **0879004A-840-21**

Ex Code

Code EAN **8054378340581**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	108lm/W
Luminaire:	56W , 6050lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.


ZOYA

opal

Arcluce Code **0879004A-840-21**

Ex Code

Code EAN **8054378340581**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 108lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

opal

Arcluce Code **0879005A-840-21**

Ex Code

Code EAN **8054378340765**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	100lm/W
Luminaire:	81W , 8100lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type VS
Color:	Aluminium - 21
Weight:	8 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




ZOYA

opal

Arcluce Code **0879005A-840-21**

Ex Code

Code EAN **8054378340765**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA



ZOYA

soft light

Arcluce Code **0879006A-840-21**

Ex Code

Code EAN **8054378340925**



Technical information

Light source:	LED, 4000K, CRI>80
Luminaire efficacy:	83lm/W
Luminaire:	42W , 3500lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Power supply:	220-240V 50/60Hz
Wiring:	ON/OFF
Optics:	type V
Color:	Aluminium - 21
Weight:	8.5 kg
Size:	A: Ø 492mm B: 640mm

CE

IP66

IK10



0,16m²

Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- PMMA lenses for LEDs.
- Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation


- Post-top installation (Ø60mm reduction).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-3.




ZOYA

soft light

Arcluce Code **0879006A-840-21**

Ex Code

Code EAN **8054378340925**



Specifications

Elegance and performance for urban lighting ZOYA is the pole top luminaire for urban lighting featuring an elegant, timeless design, excellent performance and the latest smart lighting technologies. Its diffused radial optic provides a homogeneous, pleasant lighting with high visual comfort and no glare. Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of anodized aluminium with non-iridescent specular finishing. PMMA lenses for LEDs. Shatterproof polycarbonate screen, UV-rays stabilized, V2 self-extinguishing. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-3.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 83lm/W

Luminaire in insulation class II.

DRIVER INCLUDED.

Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. ZOYA