

The Dot. family

Dot. is a family of modular components that can be retrofitted to LED applications to deliver market-leading energy savings. It is suitable for a diverse range of forms and output requirements in urban, industrial or refueling stations

up to 170lm/W
525mA

up to 165lm/W
700mA

up to 150lm/W
1050mA

1

Choose your module

4L
8 LEDs
700mA - 19W - 3.1klm
1050W - 29W - 4.4klm

8L
16 LEDs
525mA - 27W - 4.7klm
700mA - 36W - 6.0klm
1050mA - 55W - 8.5klm

12L
24 LEDs
525mA - 39W - 6.8klm
700mA - 52W - 8.8klm
1050mA - 80W - 12.3klm

24L
48 LEDs
525mA - 77W - 13.0klm
700mA - 103W - 16.8klm
1050mA - 159W - 23.6klm

2

Choose your programming

OPTION S

- Standard Programming **S**
- Custom Programming **C**
- Standard Programming **DIM***
- Dali Dimmable **DL****

VARIANT S

- No socket/No sensor **S**
- Zhaga socket D4i Driver **Z****
- Motion / ambient sensor Bluetooth fully programmable **M***

3

Choose your mounting

① Square plate with central hole
② Round plate with central hole
③ Square plate with central hole and mounting tabs
④ Square plate with central hole and mounting tabs (variant)
⑤ Square plate with central hole and mounting tabs (variant)
⑥ Square plate with central hole and mounting tabs (variant)
⑦ Square plate with central hole and mounting tabs (variant)
⑧ Square plate with central hole and mounting tabs (variant)
⑨ Square plate with central hole and mounting tabs (variant)
⑩ Square plate with central hole and mounting tabs (variant)

Dot.energy

- ① KT-REF-SQ-STD-#-WH
- ② KT-REF-CR-STD-#-WH

Dot.wall

- ③ KT-WALL-SG

Dot.multi

- ④ KT-KIT-MLT
- ⑤ KT-KIT-ADJ

Dot.fuel

- ⑥ KT-PTR-SQ-S-WH
- ⑦ KT-PTR-SQ450-#-WH
- ⑧ KT-PTR-SQ600-#-WH

Dot.fuel Gen.2

- ⑨ 44*
- ⑩ 45**

4L, 8L, 12L net lumen for K07 lens 4000K. 24L net lumen for PS lens 4000K

*Only Dot.fuel Gen.2 **Only for Dot. PLUS version

: Choose plate variant according to Dot. variant (S or Z)

*Retrofitting CPY & 304 products, in combination with existing RTF-RCS kit **Delivered pre-assembled