

OSQ Series

OSQ™ LED Wall Mount Luminaire



Product Description

The OSQ™ LED wall mount luminaire has a slim, low profile design intended for outdoor wall mounted applications. The rugged lightweight aluminum housing and mounting box are designed for installation over standard single gang J-Boxes and mud ring single gang J-Boxes. The luminaire allows for through-wired or conduit entry from the top, bottom, sides and rear. The housing design is intended specifically for LED technology including a weathertight LED driver compartment and thermal management. Optic design features industry-leading NanoComfort Technology which provides superior glare reduction and visual comfort with high-efficiency illumination delivered precisely where it is needed.

Applications: General area and security lighting

Performance Summary

Utilizes Patented NanoComfort® Technology

Utilizes Cree TrueWhite® Technology on 5000K Luminaires

Assembled in the USA by Cree Lighting from US and imported parts

Initial Delivered Lumens: Up to 8,600

Input Power: 16 - 55 watts

Efficacy: Up to 159 LPW

CRI: Minimum 70 CRI (2700K, 3000K, 4000K & 5700K); 90 CRI (5000K)

CCT: 2700K, 3000K, 4000K, 5000K, 5700K



Limited Warranty†: 10 years for luminaire/10 years for Colorfast DeltaGuard® finish/5 years for BML and ML sensors/1 year for accessories

† See <https://www.creelighting.com/resources/warranties/> for warranty terms.

Accessories

| Field-Installed |
|--|
| Beauty Plate WM-PLT12** - 12" (305mm) Square WM-PLT14** - 14" (356mm) Square - Covers holes left by incumbent wall packs |

** Must specify color



| Luminaire | Weight |
|-----------|--------|
| Standard | 4.1kg |

Ordering Information

Example: OSQW-C-2L-27K7-2M-UL-WM-BK

| OSQW | C | | | | | | | | |
|--------|--------|--|--|---|------------------------------------|-------------------|--|--|---|
| Family | Series | Lumen Package* | CCT/CRI | Optic | Voltage | Mounting | Finish | Controls** | Options |
| OSQW | C | 2L 2,550 lumens - Available only with UL voltage 4L 4,020 lumens 6L 6,075 lumens 8L 8,600 lumens | 27K7 2700K, 70 CRI 30K7 3000K, 70 CRI 40K7 4000K, 70 CRI 50K9 5000K, 90 CRI 57K7 5700K, 70 CRI | 2M Type II Mid 3M Type III Mid 4M Type IV Mid | UL Universal 120-277V | WM Wall | BK Black BZ Bronze SV Silver WH White | ML Multi-Level - Refer to ML spec sheet for details - Utilizes a multifunction sensor - Available only with UL voltage - Not available with other controls or EB option P Button Photocell - Available with UL and 34 voltages only - Not available with other controls or EB option DL DALI - Contact ADLT for more information | 20KV 20kV/10kA Surge Suppression - Replaces standard 10kV/5kA |

* Lumen Package codes identify approximate light output only. Actual lumen output levels vary depending on CCT selection. Refer to Initial Delivered Lumen tables for specific lumen values.

** Luminaire comes standard with 0-10V dimming. Controls by others.



Advanced Lighting Technologies Australia Inc
 Advanced Lighting Technologies New Zealand Ltd
 Advanced Lighting Technologies Asia Pte Ltd

Australia
 New Zealand
 Singapore

+61 3 9800 5600
 +64 9 415 6332
 +65 6844 2338

www.adlt.com.au
 www.adlt.co.nz
 www.adlt.com.sg

OSQ Series

OSQW™ LED Wall Mount Luminaire



Product Specifications

CREE LIGHTING NANOCOMFORT® TECHNOLOGY

Cree Lighting's NanoComfort® Technology ends the trade-offs in outdoor lighting by providing superior glare reduction and visual comfort in high-efficiency illumination delivered precisely where it is needed. The basic building block of NanoComfort® Technology is a compact 4x4 array of LEDs. Each of the 16 LEDs in a module is in contact with its own acrylic polymer lens to capture and precisely direct light. With NanoComfort® Technology, the acrylic optics are cut and sculpted into facets that relieve the glare and harshness while improving visual comfort – all while retaining superb efficacy and control.

CREE TRUEWHITE® TECHNOLOGY

A revolutionary way to generate high-quality white light, Cree TrueWhite® Technology is a patented approach that delivers an exclusive combination of 90+ CRI, beautiful light characteristics and lifelong color consistency, all while maintaining high luminous efficacy – a true no compromise solution.

CONSTRUCTION & MATERIALS

- Slim, low profile design
- Luminaire housing specifically designed for LED applications with advanced LED thermal management and driver
- Acrylic optic w/clear tempered glass lens
- Some versions are provided with full circuit board, but not fully populated with LEDs or optics to scale back lumen package
- Luminaire mounting box designed for installation over standard single gang J-Boxes and mud ring single gang J-Boxes
- Luminaire can also be direct mounted to a wall and surface wired
- Includes (4) 3/16" mounting holes for customer supplied hardware. Select hardware appropriate for mounting surface
- Conduit entry from top, bottom, sides, and rear
- Exclusive Colorfast DeltaGuard® finish features an E-coat epoxy primer with an ultra-durable powder topcoat, providing excellent resistance to corrosion, ultraviolet degradation and abrasion. Silver, black, white and bronze are available
- **Weight:** Standard - 9.0 lbs. (4.1kg); Emergency - 10.0 lbs. (4.5kg)
- Includes QR code on back plate which provides access to: Online installation instructions, Luminaire information (Part number, Serial number, Build date, and Warranty end date), and Warranty claim submission form
- Duplicate 1" and 2" QR code labels are included. 1" labels can be affixed inside pole bases, next to fixtures, on site plans, or in maintenance records. 2" labels can be scanned from the ground when placed at an appropriate height

ELECTRICAL SYSTEM

- **Input Voltage:** 120-277V or 347-480V, 50/60Hz
- **Power Factor:** > 0.9 at full load
- **Total Harmonic Distortion:** < 20% at full load
- Integral 10kV/5kA surge suppression protection standard; 20kV/10kA surge suppression protection optional
- When code dictates fusing, a slow blow fuse or type C/D breaker should be used to address inrush current
- Designed with 0-10V dimming capabilities. Dims to 10%. Controls by others
- 0-10V ANSI C137.1-2019 (8-Volt)
- **Maximum 10V Source Current:** 1 mA
- Refer to [Dimming spec sheet](#) for details
- **Operating Temperature Range:** -40°C - +50°C (-40°F - +122°F); Minimum operating temperature with EB option: -20°C (-4°F)

REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus Listed
- Suitable for wet locations
- Designed for downlight applications only
- UL924 (EB Option) Maximum mounting height: 20.0'(6.1m)
- Enclosure rated IP66 per IEC 60598
- ANSI C136.2 10kV/5kA (standard) and 20kV/10kA (optional) surge protection, tested in accordance with IEEE/ANSI C62.41.2
- Meets FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions
- Certified to ANSI C136.31-2001, 3G bridge and overpass vibration standards

- Luminaire and finish endurance tested to withstand 5,000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- Lens meets IK09 requirements per IEC 60068-2
- Assembled in the USA by Cree Lighting from US and imported parts
- RoHS compliant. Consult factory for additional details
- DarkSky Approved when ordered with 27K7 or 30K7 CCTs. Please refer to <https://darksky.org/what-we-do/darksky-approved/products-companies/#!/~search/keyword=cree> for most current information

| Electrical Data* | | | | | | | | | | | | |
|------------------|-------------------------|--------------|------|------|------|--------|--------|--------------------------|-------------------|------|------|------|
| Lumen Package | System Watts 120-480V** | System Watts | | | | | | EB System Watts 120-277V | Total Current (A) | | | |
| | | 120V | 208V | 240V | 277V | 347V** | 480V** | | 120V | 208V | 240V | 277V |
| 2L | 16 | 0.13 | 0.08 | 0.07 | 0.06 | N/A | N/A | 19 | 0.16 | 0.09 | 0.08 | 0.07 |
| 4L | 27 | 0.22 | 0.13 | 0.11 | 0.10 | 0.08 | 0.06 | 30 | 0.24 | 0.14 | 0.12 | 0.11 |
| 6L | 40 | 0.34 | 0.19 | 0.17 | 0.14 | 0.12 | 0.08 | 43 | 0.36 | 0.21 | 0.18 | 0.16 |
| 8L | 55 | 0.47 | 0.27 | 0.23 | 0.20 | 0.16 | 0.12 | 58 | 0.49 | 0.28 | 0.24 | 0.21 |

* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347-480V +/- 10%.

** 2L lumen package is only available with 120-277V.

OSQW Series Ambient Adjusted Lumen Maintenance Factors¹

| Ambient | Lumen Package | Initial LMF | 25K hr Reported ² LMF | 50K hr Reported ² LMF | 75K hr Reported ² LMF | 100K hr Reported ² LMF |
|---------|---------------|-------------|----------------------------------|----------------------------------|----------------------------------|-----------------------------------|
| 5°C | 2L | 1.02 | 0.99 | 0.97 | 0.94 | 0.92 |
| | 4L-8L | 1.02 | 0.99 | 0.93 | 0.88 | 0.83 |
| 10°C | 2L | 1.02 | 0.99 | 0.96 | 0.94 | 0.91 |
| | 4L-8L | 1.02 | 0.98 | 0.93 | 0.87 | 0.82 |
| 15°C | 2L | 1.01 | 0.98 | 0.96 | 0.93 | 0.91 |
| | 4L-8L | 1.01 | 0.98 | 0.92 | 0.87 | 0.82 |
| 20°C | 2L | 1.01 | 0.97 | 0.95 | 0.93 | 0.90 |
| | 4L-8L | 1.01 | 0.97 | 0.92 | 0.86 | 0.81 |
| 25°C | 2L | 1.00 | 0.97 | 0.94 | 0.92 | 0.90 |
| | 4L-8L | 1.00 | 0.97 | 0.91 | 0.86 | 0.81 |
| 30°C | 2L | 0.99 | 0.96 | 0.94 | 0.91 | 0.89 |
| | 4L-8L | 0.99 | 0.96 | 0.90 | 0.85 | 0.80 |
| 35°C | 2L | 0.99 | 0.96 | 0.93 | 0.91 | 0.89 |
| | 4L-8L | 0.99 | 0.95 | 0.90 | 0.85 | 0.80 |
| 40°C | 2L | 0.98 | 0.95 | 0.93 | 0.90 | 0.88 |
| | 4L-8L | 0.98 | 0.95 | 0.89 | 0.84 | 0.79 |
| 45°C | 2L | 0.98 | 0.95 | 0.92 | 0.90 | 0.87 |
| | 4L-8L | 0.98 | 0.94 | 0.89 | 0.84 | 0.79 |
| 50°C | 2L | 0.97 | 0.94 | 0.91 | 0.89 | 0.87 |
| | 4L-8L | 0.97 | 0.94 | 0.88 | 0.83 | 0.79 |

¹ Lumen maintenance values at 25°C (77°F) are calculated per IES TM-21 based on IES LM-80 report data for the LED package and in-situ luminaire testing. Luminaire ambient temperature factors (LATF) have been applied to all lumen maintenance factors. Please refer to the [Temperature Zone Reference Document](#) for outdoor average nighttime ambient conditions.

² In accordance with IES TM-21, Reported values represent interpolated values based on time durations that are up to 6x the tested duration in the IES LM-80 report for the LED.

| Delivered Emergency Lumens | | | | |
|----------------------------|---------------------|---------------|---------------|---------------|
| Lumen Package | CCT/CRI | | | |
| | 2700K/3000K, 70 CRI | 4000K, 70 CRI | 5000K, 90 CRI | 5700K, 70 CRI |
| 2L | 1,070 | 1,120 | 810 | 1,120 |
| 4L | 1,000 | 1,040 | 760 | 1,040 |
| 6L | 1,020 | 1,060 | 780 | 1,060 |
| 8L | 1,110 | 1,160 | 800 | 1,160 |



Advanced Lighting Technologies Australia Inc
Advanced Lighting Technologies New Zealand Ltd
Advanced Lighting Technologies Asia Pte Ltd

Australia
New Zealand
Singapore

+61 3 9800 5600
+64 9 415 6332
+65 6844 2338

www.adlt.com.au
www.adlt.co.nz
www.adlt.com.sg

OSQ Series


OSQW™ LED Wall Mount Luminaire




Photometry

All published luminaire photometric testing performed to IES LM-79 standards. To obtain an IES file specific to your project consult: <https://www.creelighting.com/products/outdoor/wall-mount/osq-series-2/>

2M



RESTL Test Report #: PL18035-001A
OSQW-C-8L-30K7-2M-UL-WM-WH
Initial Delivered Lumens: 8,577




OSQW-C-4L-40K7-2M-Ux-WM-xx-xx
Mounting Height: 15' (4.6) A.F.G.
Initial Delivered Lumens: 4,020
Initial FC at grade


| Type II Mid Distribution | | | | | | | | |
|--------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|
| Lumen Package | 2700K/3000K, 70CRI | | 4000K, 70CRI | | 5000K, 90CRI | | 5700K, 70CRI | |
| | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 |
| 2L | 2,450 | B1 U0 G1 | 2,550 | B1 U0 G1 | 1,860 | B1 U0 G1 | 2,550 | B1 U0 G1 |
| 4L | 3,870 | B1 U0 G1 | 4,020 | B1 U0 G1 | 2,940 | B1 U0 G1 | 4,020 | B1 U0 G1 |
| 6L | 5,825 | B1 U0 G1 | 6,075 | B1 U0 G1 | 4,430 | B1 U0 G1 | 6,075 | B1 U0 G1 |
| 8L | 8,250 | B2 U0 G2 | 8,600 | B2 U0 G2 | 6,275 | B1 U0 G1 | 8,600 | B2 U0 G2 |

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

3M



RESTL Test Report #: PL18036-001A
OSQW-C-8L-30K7-3M-UL-WM-WH
Initial Delivered Lumens: 8,543



OSQW-C-4L-40K7-3M-Ux-WM-xx-xx
Mounting Height: 15' (4.6) A.F.G.
Initial Delivered Lumens: 4,020
Initial FC at grade

| Type III Mid Distribution | | | | | | | | |
|---------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|
| Lumen Package | 2700K/3000K, 70CRI | | 4000K, 70CRI | | 5000K, 90CRI | | 5700K, 70CRI | |
| | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 |
| 2L | 2,450 | B1 U0 G1 | 2,550 | B1 U0 G1 | 1,860 | B1 U0 G1 | 2,550 | B1 U0 G1 |
| 4L | 3,870 | B1 U0 G1 | 4,020 | B1 U0 G1 | 2,940 | B1 U0 G1 | 4,020 | B1 U0 G1 |
| 6L | 5,825 | B1 U0 G1 | 6,075 | B1 U0 G1 | 4,430 | B1 U0 G1 | 6,075 | B1 U0 G1 |
| 8L | 8,250 | B2 U0 G2 | 8,600 | B2 U0 G2 | 6,275 | B1 U0 G1 | 8,600 | B2 U0 G2 |

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



Advanced Lighting Technologies Australia Inc
Advanced Lighting Technologies New Zealand Ltd
Advanced Lighting Technologies Asia Pte Ltd

Australia
New Zealand
Singapore


+61 3 9800 5600
+64 9 415 6332
+65 6844 2338

www.adlt.com.au
www.adlt.co.nz
www.adlt.com.sg


Photometry

All published luminaire photometric testing performed to IES LM-79 standards. To obtain an IES file specific to your project consult:
<https://www.creelighting.com/products/outdoor/wall-mount/osq-series-2/>

4M



RESTL Test Report #: PL18037-001A
 OSQW-C-8L-30K7-4M-UL-WM-WH
 Initial Delivered Lumens: 8,441



OSQW-C-4L-40K7-4M-Ux-WM-xx-xx
 Mounting Height: 15' (4.6) A.F.G.
 Initial Delivered Lumens: 4,020
 Initial FC at grade

| Type IV Mid Distribution | | | | | | | | |
|--------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|---------------------------|----------------------------|
| Lumen Package | 2700K/3000K, 70CRI | | 4000K, 70CRI | | 5000K, 90CRI | | 5700K, 70CRI | |
| | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 | Initial Delivered Lumens* | BUG Ratings** Per TM-15-20 |
| 2L | 2,450 | B1 U0 G1 | 2,550 | B1 U0 G1 | 1,860 | B1 U0 G1 | 2,550 | B1 U0 G1 |
| 4L | 3,870 | B1 U0 G1 | 4,020 | B1 U0 G1 | 2,940 | B1 U0 G1 | 4,020 | B1 U0 G1 |
| 6L | 5,825 | B1 U0 G1 | 6,075 | B1 U0 G1 | 4,430 | B1 U0 G1 | 6,075 | B1 U0 G1 |
| 8L | 8,250 | B2 U0 G2 | 8,600 | B2 U0 G2 | 6,275 | B1 U0 G1 | 8,600 | B2 U0 G2 |

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.
 ** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>.

| Replacement Parts | |
|---|---|
| EB Replacement Kit OSQW-C-EBKIT - Suitable for use with all lumen packages and UL voltage | Back Box Replacement Kit OSQW-C-JBOXKIT - Suitable for use with all OSQW-C luminaires |

| Driver Replacement Parts | | |
|--------------------------|---|-----------------------|
| Product | Lumen Package | Voltage |
| OSQW-C-DVRKT | 2L 2,550 Lumens - Available only with UL voltage | UL 120-277V |
| | 4L 4,020 Lumens | |
| | 6L 6,075 Lumens | |
| | 8L 8,600 Lumens | |

© 2024 Cree Lighting USA LLC. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. Colorfast DeltaGuard® and NanoComfort® are registered trademarks, and OSQW™ is a trademark of Cree Lighting USA LLC. TrueWhite®, Cree TrueWhite® and the Cree TrueWhite Technology logo are registered trademarks of CREELED, Inc. Cree® and the Cree logo are registered trademarks of SMART Global Holdings, Inc. The UL logo is a registered trademark of UL LLC. Synapse® is a registered trademark of Synapse Wireless, Inc. Verizon® is a registered trademark of Verizon Trademark Services LLC. DarkSky and the DarkSky Approved logo are trademarks of DarkSky International. LEVITON® is a registered trademark of Leviton Manufacturing Co., Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks is under license. Other trademarks, service marks, and trade names are those of their respective owners. IOS is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries. Apple and App Store are trademarks of Apple Inc. Android is a trademark of Google, Inc.