

# KATLA BL

## PROFILE LUMINAIRE



SEALS

Extremely short silicone seals

ALUMINIUM CARRIER

For optimal thermal management

THROUGH-WIRING

3x1,5mm² ex factory

VARIABLE

PRACHT-CLIP-SYSTEM  
for variable mounting

IK08

Co-extruded  
polycarbonate housing

QUICK CONNECTION

Due to clippable end caps  
and PRACHT SLIDER

ALLROUNDER

**HOUSING** Co-extruded polycarbonate, impact resistant, IK08.  
**SEALS** Extremely short, ageing resistant silicone seals.  
**ELECTRICAL COMPONENTS** High power LED, LED converter.  
**THROUGH-WIRING** Including 3x1,5 mm² wiring ex factory.  
**ASSEMBLY** Variable mounting distances with PRACHT-CLIP-SYSTEM.  
Suitable for ceiling and rail mounting.  
**FIELDS OF APPLICATION** Parking garages, basements, workshops, 1:1  
fluorescent light exchange.

- SLIM HOUSING
- STABLE
- 1:1 EXCHANGE
- ENEC
- SIMPLE MOUNTING
- HOMOGENEOUS LIGHT

**KATLA BL** Individual luminaire, color temperature 4000 K, Ra>80, IP65, -20°C ... +40°C

Power	Light distribution	Luminous flux	P/N	Length
1x20 W	120° wide	2800 lm	5231004B	1240 mm
1x38 W	120° wide	5400 lm	5231014B	1240 mm
1x27 W	120° wide	3800 lm	5231005B	1540 mm
1x46 W	120° wide	6500 lm	5231015B	1540 mm

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT



Protection class I according to EN 60598  
Protection type IP65  
AC 220-240 V 50/60 Hz

Advanced Lighting Technologies is an authorised distributor of PRACHT