

LUNA BL

DIFFUSER LUMINAIRE



HOUSING Polycarbonate, impact-resistant, IK08.
LAMP COVER Polycarbonate with integrated LED unit.
SEALS Non-ageing silicone seals.
ELECTRICAL COMPONENTS High-performance LED, LED converter.
ASSEMBLY Variable mounting distances thanks to the PRACHT CLAMPING SYSTEM. Suitable for ceiling, wall, pendant and rail mounting.
AREAS OF APPLICATION Parking garages, cellars, workshops, 1:1 LL replacement.
EL-CERTIFIED The LUNA BL is suitable for emergency lighting

- HIGH QUALITY
- QUICK ASSEMBLY
- 1:1 EXCHANGE
- ENEC
- DUST-TIGHT
- EL-CERTIFIED
- HOMOGENEOUS LIGHT


FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT



Protection class I according to EN 60598
Protection type IP65
AC 220-240 V 50/60 Hz



IP65



LUNA BL

Single luminaire, color temperature 4000 K, Ra>80, IP65, -20°C ... +40°C

Power	Light distribution	Luminous flux	P/N	Length
1x20 W	120° wide	2500 lm	5211012	600 mm
1x20 W	120° wide	2800 lm	5211004B	1200 mm
1x39 W	120° wide	5400 lm	5211014B	1200 mm
1x27 W	120° wide	3800 lm	5211005B	1500 mm
1x47 W	120° wide	6500 lm	5211015B	1500 mm

ACCESSORIES

Through-wiring	P/N
3x1,5mm² Set LUNA BL 1,2m, consisting of rigid conductors, 2x5pin terminal block	5552132
3x1,5mm² Set LUNA BL 1,5m, consisting of rigid conductors, 2x5pin terminal block	5552135
5x2,5mm² Set LUNA BL 1,2m, consisting of rigid conductors, 2x5pin terminal block	5552152
5x2,5mm² Set LUNA BL 1,5m, consisting of rigid conductors, 2x5pin terminal block	5552155