

LUNA BL ONE

THE FIRST **DIFFUSER LIGHT**
MADE FROM UP TO **98 % RECYCLATE**



THE LIGHT OF THE
FUTURE
A VIEW OF LIGHT FOR
THE ENVIRONMENT

SUSTAINABLE LIGHT FOR ALL

Ready for the requirements of the future:
recycled content up to 98%,
efficiency up to 180 lm/W

VERSATILE

Also available as a version with multilumen,
DALI, TW and sensor

HOUSING PC recyclate, impact-resistant, IK08, REMADE SCORE 98%.
COVER PC recyclate with integrated LED unit.
SEALS Non-ageing silicone seals.
ELECTRICAL COMPONENTS High-power LED, LED converter.
ASSEMBLY Variable fixing distances with PRACHT-KLAMMER-SYSTEM. Suitable for ceiling, wall, pendant and mounting rail installation.
AREAS OF APPLICATION Parking garages, industry, production, warehouses, workshops, 1:1 FL replacement.
EL-CERTIFIED The LUNA BL is suitable for emergency lighting.

- **SUSTAINABLE - MADE FROM UP TO 98 % RECYCLED MATERIAL**
- **QUICK ASSEMBLY**
- **1:1 EXCHANGE**
- **ENEC**
- **DUST-TIGHT**
- **EL-CERTIFIED**
- **HOMOGENEOUS LIGHT**

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT



ENEC registered

Protection class I according to EN 60598
Ingress Protection IP65



PRACHT LUNA BL ONE

Single luminaire, color temperature 4000 K, R_a>80, IP65, -20°C ... +40°C

Art.-No.	Execution	Luminous flux	Light distribution	Length	Through-wiring
5800222	DIP SWITCH	1250 - 2500lm	120° breit	600 mm	–
5852222	DIP SWITCH + SENSOR	1250 - 2500lm	120° breit	600 mm	4x1,5 mm ²
5800114	ON/OFF	2800 lm	120° breit	1200 mm	–
5800224	DIP SWITCH	2800 - 5400 lm	120° breit	1200 mm	–
5880224	DIP SWITCH + DV	2800 - 5400 lm	120° breit	1200 mm	5x2,5 mm ²
5880129	DALI + DV	5400 lm	120° breit	1200 mm	5x2,5 + 2x1,5 mm ²
5852224	DIP SWITCH + SENSOR	2800 - 5400 lm	120° breit	1200 mm	4x1,5 mm ²
5832129	DALI + SENSOR	2800 - 5400 lm	120° breit	1200 mm	5x1,5 mm ²
5800234	DIP SWITCH	5400 - 8400 lm	120° breit	1200 mm	–
5880234	DIP SWITCH + DV	5400 - 8400 lm	120° breit	1200 mm	5x2,5 mm ²
5880139	DALI + DV	8400 lm	120° breit	1200 mm	5x2,5 + 2x1,5 mm ²
5852234	DIP SWITCH + SENSOR	5400 - 8400 lm	120° breit	1200 mm	4x1,5 mm ²
5800115	ON/OFF	3800 lm	120° breit	1500 mm	–
5800225	DIP SWITCH	3800 - 6500 lm	120° breit	1500 mm	–
5880225	DIP SWITCH + DV	3800 - 6500 lm	120° breit	1500 mm	5x2,5 mm ²
5880120	DALI + DV	6500 lm	120° breit	1500 mm	5x2,5 + 2x1,5 mm ²
5852225	DIP SWITCH + SENSOR	3800 - 6500 lm	120° breit	1500 mm	4x1,5 mm ²
5832120	DALI + SENSOR	3800 - 6500 lm	120° breit	1500 mm	5x1,5 mm ²
5800235	DIP SWITCH	6500 - 11500 lm	120° breit	1500 mm	–
5880235	DIP SWITCH + DV	6500 - 11500 lm	120° breit	1500 mm	5x2,5 mm ²
5880130	DALI + DV	12000 lm	120° breit	1500 mm	5x2,5 + 2x1,5 mm ²
5852235	DIP SWITCH + SENSOR	6500 - 11500 lm	120° breit	1500 mm	4x1,5 mm ²