

PRO LINE

LIGHT FOR THE EXTREME



**CUSTOMIZED
SOLUTIONS FOR
EXTREME
REQUIRMENTS**

1 MANUFACTURER 4 SEGMENTS OVER 4000 LUMINAIRES

THE RIGHT LUMINAIRE FOR EVERY REQUIREMENT

LARGEST WET ROOM RANGE IN EUROPE

A luminaire range from light for every day use up to tailor-made individual solutions for extreme demands. A portfolio for all requirements.

ECONOMICAL & EFFICIENT

In terms of purchase and maintenance. PRACHT luminaires stand for high efficiency at the best price-performance ratio.

BRAND QUALITY

100 years of experience make PRACHT the first port of call for damp-proof luminaires

GREEN INNOVATION

Transparent sustainability and energy efficiency - Long-life components, recycled materials (REMADE), easy to replace exchangeability of electronics (REUSE) and a high level of material expertise are the hallmarks of PRACHT's sustainable offering

ECO LINE LIGHT FOR EVERYDAY LIFE

**ECONOMIC.
EASY.
EFFICIENT.**

Full-LED and RETRO-FIT luminaire in one unbeatable price-performance ratio:

- Cellars
- Corridors
- Technical rooms
- Garages
- Warehouse



BASIC LINE LIGHT FOR PROFESSIONALS



High-quality, industrial-grade luminaires for easy installation

- Unprotected outdoor areas
- Production areas
- Agricultures
- Logistics
- Underground garages
- Warehouses
- Pits
- Car washes
- Corridors
- Side rooms



PRO LINE LIGHT FOR THE EXTREME



Industrial luminaires of the highest quality, durability and robustness. Customizable depending on individual requirements. Warranty 5 Years+

- Demanding industrial sectors such as food & beverages
- Potentially explosive areas
- Chemical & noxious gas contaminated environments
- High & low temperatures
- Vandalism protected
- Electroplatings
- Transportation companies




ONECONNECT LIGHTING SYSTEMS

**STANDARD
SYSTEM**

ONE CONNECT, made from 99% recycled material, turns individual luminaires into a variety of lighting systems and shapes

- Reception & recreation areas
- Offices
- Garages
- Cellars
- Corridors & hallways
- Technical rooms & workshops



SECTORS

LIGHT FOR THE EXTREME

Customised lighting solutions for special requirements and areas of application - that's what the PRO LINE from PRACHT stands for. Resistance to heat, cold, aggressive gases and liquids or the guarantee of safety are just a few examples of the special performance of the luminaires from the PRACHT PRO LINE. Networked and controlled IOT solutions are also part of the segment as well as the fulfilment of many other requirements.

In a nutshell: The PRO LINE starts where others stop. With a guarantee of 5 years and more, these luminaires stand for the highest quality MADE IN GERMANY and combine the PRACHT expertise of many decades in the development of reliable and innovative lighting solutions. PRACHT is the first and only manufacturer in the world to offer industrial-grade lighting solutions made from up to 99% recycled material in the PRO LINE. We will be happy to introduce you to many other sustainability initiatives along the product life cycle, such as the interchangeability of components or refurbishing options.

High quality advice and project support are particularly important in project lighting. As a medium-sized family business we place the highest value on accessibility, short distances and a trusting and reliable working relationship.



TRANSPORT SERVICES

FOOD & BEVERAGE

AGRICULTURE

LOGISTICS

HEAVY DUTY

MULTI-STOREY CAR PARKS

SWIMMING POOLS

SPORTS FACILITIES

EX-PROOF AREAS

VANDALISM PROTECTION



APOLLO

G2 | G2 INDUSTRY | REMADE

HOUSING Fully sealed housing made of white, glass fiber reinforced polyester, hardly flammable, substantially acid and alkali resistant or REMADE.

LAMP HOLDER END PIECES With PRACHT EASY CONNECT (PEC) System for fast one-man-mounting via encoded plug-in connection.

LAMP COVER With parabolic mirror reflector, swivelling, made of PRACHTOPAL® (impact resistant), clear PMMA (deep 30°) or REMADE.

SEALS Short, ageing resistant silicone seals.

ELECTRICAL COMPONENTS Thermic decoupled high performance LEDs and converters.

THROUGH-WIRING 7x2.5 mm² max. available.



INSTALLATION Variable mounting points due to PRACHT-CLIP-SYSTEM made of stainless steel. Suitable for ceiling, pendant and horizontal wall mounting. Optionally available as a recessed version.

FIELDS OF APPLICATION Industrial halls, logistic centers, cold storage facilities, workshops, maintenance and production halls.

DETERMINED


Swivelling reflectors ensure perfect illumination.

PRACHT®




VERSATILE

A matter of definition - Through-wiring, sensors, emergency light, everything is possible.



TIME IS MONEY

Time-saving thanks to the PEC- System and optional Plug'n Play (pnp) Quick Exchange Converter.



PRACHT EASY CONNECT (PET) SYSTEM

Revolutionized guided plug-in connection for one-man-mounting ensuring the simplest reflector installation.

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

FOR EVERYDAY LIFE
Cost-effective and easy to assemble

BASIC LINE

FOR PROFESSIONALS
Industrial quality with 5 year PRACHT warranty

PRO LINE

FOR THE EXTREME
Customised solutions & highest requirements

5

YEAR WARRANTY



UP TO 100.000 h LIFETIME

ENERGY EFFICIENCY CLASS

IP65

RECYCLED 98% OLD PLASTIC

REMADESCORE



FROM -45 °C TO +65 °C DEPENDING ON MODEL

APOLLO G2

from -20° to +45° C, 1260 mm length, Ra > 80, color temperature 4000 K, with one reflector (180° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight
	1x14 W	2600 lm	94 * 0014w	94 * 0014m	94 * 0014n	94 * 1014d	2,7 kg
	1x22 W	3700 lm	94 * 0024w	94 * 0024m	94 * 0024n	94 * 1024d	2,7 kg
	1x28 W	4800 lm	94 * 0034w	94 * 0034m	94 * 0034n	94 * 1034d	2,7 kg
	1x36 W	5800 lm	94 * 0044w	94 * 0044m	94 * 0044n	94 * 1044d	2,7 kg
	1x51 W	8100 lm	94 * 0054w	94 * 0054m	94 * 0054n	94 * 1054d	2,7 kg
DIM-DALI	1x14 W	2600 lm	94 * 0019w	94 * 0019m	94 * 0019n	94 * 1019d	2,7 kg
	1x22 W	3700 lm	94 * 0029w	94 * 0029m	94 * 0029n	94 * 1029d	2,7 kg
	1x28 W	4800 lm	94 * 0039w	94 * 0039m	94 * 0039n	94 * 1039d	2,7 kg
	1x36 W	5800 lm	94 * 0049w	94 * 0049m	94 * 0049n	94 * 1049d	2,7 kg
	1x51 W	8100 lm	94 * 0059w	94 * 0059m	94 * 0059n	94 * 1059d	2,7 kg

APOLLO G2

from -20° to +45° C, 1260 mm length, Ra > 80, color temperature 4000 K, with two reflectors (each 160° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight
	2x14 W	5200 lm	94 * 0074w	94 * 0074m	94 * 0074n	94 * 1074d	4,4 kg
	2x21 W	7400 lm	94 * 0084w	94 * 0084m	94 * 0084n	94 * 1084d	4,4 kg
	2x28 W	9600 lm	94 * 0094w	94 * 0094m	94 * 0094n	94 * 1094d	4,4 kg
	2x36 W	11600 lm	94 * 0004w	94 * 0004m	94 * 0004n	94 * 1004d	4,4 kg
	2x51 W	16200 lm	94 * 00a4w	94 * 00a4m	94 * 00a4n	94 * 1004d	4,4 kg
DIM-DALI	2x14 W	5200 lm	94 * 0079w	94 * 0079m	94 * 0079n	94 * 1079d	4,4 kg
	2x21 W	7400 lm	94 * 0089w	94 * 0089m	94 * 0089n	94 * 1089d	4,4 kg
	2x28 W	9600 lm	94 * 0099w	94 * 0099m	94 * 0099n	94 * 1099d	4,4 kg
	2x36 W	11600 lm	94 * 0009w	94 * 0009m	94 * 0009n	94 * 1009d	4,4 kg
	2x51 W	16200 lm	94 * 00a9w	94 * 00a9m	94 * 00a9n	94 * 10a9d	4,4 kg

APOLLO G2

from -20° to +45° C, 1560 mm length, Ra > 80, color temperature 4000 K, with one reflector (180° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight
	1x27 W	4700 lm	 94 * 0025w	94 * 0025m	94 * 0025n	94 * 1025d	3,1 kg
	1x36 W	6000 lm	94 * 0035w	94 * 0035m	94 * 0035n	94 * 1035d	3,1 kg
	1x44 W	7200 lm	 94 * 0045w	94 * 0045m	94 * 0045n	94 * 1045d	3,1 kg
	1x64 W	10200 lm	94 * 0055w	94 * 0055m	94 * 0055n	94 * 1055d	3,1 kg
	1x86 W	12500 lm	94 * 0065w	94 * 0065m	94 * 0065n	94 * 1065d	3,1 kg
DIM-DALI	1x99 W	15000 lm	94 * 00c5w	94 * 00c5m	94 * 00c5n	94 * 10c5d	3,1 kg
	1x27 W	4700 lm	94 * 0020w	94 * 0020m	94* 0020n	94 * 1020d	3,1 kg
	1x36 W	6000 lm	94 * 0030w	94 * 0030m	94 * 0030n	94 * 1030d	3,1 kg
	1x44W	7200 lm	94 * 0040w	94 * 0040m	94 * 0040n	94 * 1040d	3,1 kg
	1x64 W	10200 lm	94 * 0050w	94 * 0050m	94 * 0050n	94 * 1050d	3,1 kg
	1x86 W	12500 lm	94 * 0060w	94 * 0060m	94 * 0060n	94 * 1060d	3,1 kg
	1x99 W	15000 lm	94 * 00c0w	94 * 00c0m	94 * 00c0n	94 * 10c0d	3,1 kg

APOLLO G2

from -20° to +45° C, 1560 mm length, Ra > 80, color temperature 4000 K, with two reflectors (each 160° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight
	2x27 W	9400 lm	94 * 0085w	94 * 0085m	94 * 0085n	94 * 1085d	4,7 kg
	2x36 W	12000 lm	94 * 0095w	94 * 0095m	94 * 0095n	94 * 1095d	4,7 kg
	2x44 W	14400 lm	 94 * 0005w	94 * 0005m	94 * 0005n	94 * 1005d	4,7 kg
	2x64 W	20400 lm	94 * 00a5w	94 * 00a5m	94 * 00a5n	94 * 10a5d	4,7 kg
	2x86 W	25000 lm	94 * 00b5w	94 * 00b5m	94* 00b5n	94 * 10b5d	4,7 kg
DIM-DALI	2x99 W	30000 lm	94 * 00d5w	94 * 00d5m	94 * 00d5n	94 * 10d5d	4,7 kg
	2x27 W	9400 lm	94 * 0080w	94 * 0080m	94 * 0080n	94 * 1080d	4,7 kg
	2x36 W	12000 lm	94 * 0090w	94 * 0090m	94 * 0090n	94 * 1090d	4,7 kg
	2x44 W	14400 lm	94 * 0000w	94 * 0000m	94 * 0000n	94 * 1000d	4,7 kg
	2x64 W	20400 lm	94 * 00a0w	94 * 00a0m	94 * 00a0n	94 * 10a0d	4,7 kg
	2x86 W	25000 lm	94 * 00b0w	94 * 00b0m	94 * 00b0n	94 * 10b0d	4,7 kg
	2x99 W	30000 lm	94 * 00d0w	94 * 00d0m	94 * 00d0n	94 * 10d0d	4,7 kg

APOLLO G2 INDUSTRY

from -45° to +65° C, 1260 mm length, color temperature 4000 K, with one reflector (180° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight	Temperature
	1x21 W	3700 lm	94 * 0224w	94 * 0224m	94 * 0224n	94 * 0224d	2,7 kg	-45° to +65° C
	1x31 W	4800 lm	94 * 0234w	94 * 0234m	94 * 0234n	94 * 0234d	2,7 kg	-45° to +65° C
	1x38 W	5800 lm	94 * 0244w	94 * 0244m	94 * 0244n	94 * 0244d	2,7 kg	-45° to +60° C
	1x55 W	8100 lm	94 * 0254w	94 * 0254m	94 * 0254n	94 * 0254d	2,7 kg	-45° to +55° C
DIM-DALI	1x21 W	3700 lm	94 * 0229w	94 * 0229m	94 * 0229n	94 * 0229d	2,7 kg	-45° to +65° C
	1x31 W	4800 lm	94 * 0239w	94 * 0239m	94 * 0239n	94 * 0239d	2,7 kg	-45° to +65° C
	1x38 W	5800 lm	94 * 0249w	94 * 0249m	94 * 0249n	94 * 0249d	2,7 kg	-45° to +60° C
	1x55 W	8100 lm	94 * 0259w	94 * 0259m	94 * 0259n	94 * 0259d	2,7 kg	-45° to +55° C

APOLLO G2 INDUSTRY

from -45° to +65° C, 1260 mm length, color temperature 4000 K, with two reflectors (each 160° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight	Temperature
	2x21 W	7400 lm	94 * 0284w	94 * 0284m	94 * 0284n	94 * 0284d	3,7 kg	-45° to +65° C
	2x31 W	9600 lm	94 * 0294w	94 * 0294m	94 * 0294n	94 * 0294d	3,7 kg	-45° to +60° C
	2x38 W	11600 lm	94 * 0204w	94 * 0204m	94 * 0204n	94 * 0204d	3,7 kg	-45° to +60° C
	2x55 W	16200 lm	94 * 02a4w	94 * 02a4m	94 * 02a4n	94 * 02a4d	3,7 kg	-45° to +50° C
DIM-DALI	2x21 W	7400 lm	94 * 0289w	94 * 0289m	94 * 0289n	94 * 0289d	3,7 kg	-45° to +65° C
	2x31 W	9600 lm	94 * 0299w	94 * 0299m	94 * 0299n	94 * 0299d	3,7 kg	-45° to +60° C
	2x38 W	11600 lm	94 * 0209w	94 * 0209m	94 * 0209n	94 * 0209d	3,7 kg	-45° to +60° C
	2x55 W	16200 lm	94 * 02a9w	94 * 02a9m	94 * 02a9n	94 * 02a9d	3,7 kg	-45° to +50° C

APOLLO G2 INDUSTRY



from -45° to +65° C, 1560 mm length, color temperature 4000 K, with one reflector (180° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight	Temperature
	1x29 W	4700 lm	94 * 0225w	94 * 0225m	94 * 0225n	94 * 0225d	3,1 kg	-45° to +65° C
	1x38 W	6000 lm	94 * 0235w	94 * 0235m	94 * 0235n	94 * 0235d	3,1 kg	-45° to +65° C
	1x46 W	7200 lm	94 * 0245w	94 * 0245m	94 * 0245n	94 * 0245d	3,1 kg	-45° to +60 C
	1x70 W	10200 lm	94 * 0255w	94 * 0255m	94 * 0255n	94 * 0255d	3,1 kg	-45° to +50 C
	1x83 W	12500 lm	94 * 0265w	94 * 0265m	94 * 0265n	94 * 0265d	3,1 kg	-45° to +50 C
DIM-DALI	1x29 W	4700 lm	94 * 0220w	94 * 0220m	94 * 0220n	94 * 0220d	3,1 kg	-45° to +65° C
	1x38 W	6000 lm	94 * 0230w	94 * 0230m	94 * 0230n	94 * 0230d	3,1 kg	-45° to +65° C
	1x46 W	7200 lm	94 * 0240w	94 * 0240m	94 * 0240n	94 * 0240d	3,1 kg	-45° to +65° C
	1x70 W	10200 lm	94 * 0250w	94 * 0250m	94 * 0250n	94 * 0250d	3,1 kg	-45° to +65° C
	1x83 W	12500 lm	94 * 0260w	94 * 0250m	94 * 0260n	94 * 0260d	3,1 kg	-45° to +65° C

APOLLO G2 INDUSTRY

from -45° to +65° C, 1560 mm length, color temperature 4000 K, with two reflectors (each 160° swivelling).

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Narrow 30°	Weight	Temperature
	2x29 W	9400 lm	94 * 0285w	94 * 0285m	94 * 0285n	94 * 0285d	4,2 kg	-45° to +65° C
	2x38 W	12000 lm	94 * 0295w	94 * 0295m	94 * 0295n	94 * 0295d	4,2 kg	-45° to +60° C
	2x46 W	14400 lm	94 * 0205w	94 * 0205m	94 * 0205n	94 * 0205d	4,2 kg	-45° to +55° C
	2x70 W	20400 lm	94 * 02a5w	94 * 02a5m	94 * 02a5n	94 * 02a5d	4,2 kg	-45° to +50° C
	2x83 W	25000 lm	94 * 02b5w	94 * 02b5m	94 * 02b5n	94 * 02b5d	4,2 kg	-45° to +50° C
DIM-DALI	2x29 W	9400 lm	94 * 0280w	94 * 0280m	94 * 0280n	94 * 0280d	4,2 kg	-45° to +65° C
	2x38 W	12000 lm	94 * 0290w	94 * 0290m	94 * 0290n	94 * 0290d	4,2 kg	-45° to +60° C
	2x46 W	14400 lm	94 * 0200w	94 * 0200m	94 * 0200n	94 * 0200d	4,2 kg	-45° to +55° C
	2x70 W	20400 lm	94 * 02a0w	94 * 02a0m	94 * 02a0n	94 * 02a0d	4,2 kg	-45° to +50° C
	2x83 W	25000 lm	94 * 02b0w	94 * 02b0m	94 * 02b0n	94 * 02b0d	4,2 kg	-45° to +50° C



APOLLO REMADE

with one reflector (180° swivelling), 600 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x21 W	3000 lm	94 * 5042w	94 * 5042m	94 * 5042n	2,0 kg
	1x21 W	3000 lm	94 * 5047w	94 * 5047m	94 * 5047n	2,0 kg

APOLLO REMADE

with one reflector (180° swivelling), 1200 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

DIM-DALI	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x36 W	5800 lm	94 * 5044w	94 * 5044m	94 * 5044n	2,7 kg
	1x36 W	5800 lm	94 * 5049w	94 * 5049m	94 * 5049n	2,7 kg

APOLLO REMADE

with two reflectors (180° swivelling), 1200 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	2x36 W	11600 lm	94 * 5004w	94 * 5004m	94 * 5004n	4,4 kg
	2x36 W	11600 lm	94 * 5009w	94 * 5009m	94 * 5009n	4,4 kg

APOLLO REMADE

with one reflector (180° swivelling), 1500 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

DIM-DALI	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x44 W	7200 lm	94 * 5045w	94 * 5045m	94 * 5045n	3,1 kg
	1x44 W	7200 lm	94 * 5049w	94 * 5040m	94 * 5040n	3,1 kg

APOLLO REMADE

with two reflectors (180° swivelling), 1500 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	2x44 W	14400 lm	94 * 5005w	94 * 5005m	94 * 5005n	4,7 kg
	2x44 W	14400 lm	94 * 5000w	94 * 5000m	94 * 5000n	4,7 kg

APOLLO G2 ULTRA

with one reflector (180° swivelling), 600 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

DIM-DALI	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x18 W	3600 lm	94 * 0132w	94 * 0132m	94 * 0132n	2,0 kg
	1x18 W	3600 lm	94 * 0137w	94 * 0137m	94 * 0137n	2,0 kg

APOLLO G2 ULTRA

with one reflector (180° swivelling), 1200 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x34 W	7200 lm	94 * 0134w	94 * 0134m	94 * 0134n	2,7 kg
	1x34 W	7200 lm	94 * 0139w	94 * 0139m	94 * 0139n	2,7 kg

APOLLO G2 ULTRA

with two reflectors (180° swivelling), 1200 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

DIM-DALI	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	2x33 W	14400 lm	94 * 0174w	94 * 0174m	94 * 0174n	4,4 kg
	2x33 W	11400 lm	94 * 0179w	94 * 0179m	94 * 0179n	4,4 kg

APOLLO G2 ULTRA

with one reflector (180° swivelling), 1500 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

ON/OFF	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	1x42 W	8900 lm	94 * 0135w	94 * 0135m	94 * 0135n	3,1 kg
	1x42 W	8900 lm	94 * 0130w	94 * 0130m	94 * 0130n	3,1 kg

APOLLO G2 ULTRA

with two reflectors (180° swivel), 1500 mm length, R_a > 80, color temperature 4000 K, Ta: -20°C ... +45°C.

DIM-DALI	Power	Luminous flux	Wide 90°	Medium 80°	Deep 60°	Weight
	2x41 W	17800 lm	94 * 0175w	94 * 0175m	94 * 0175n	4,7 kg
	2x41 W	17800 lm	94 * 0170w	94 * 0170m	94 * 0170n	4,7 kg



NOTE

Please replace the asterisk * with the needed digit to complete the P/N!

OTHER LIGHT COLORS AVAILABLE ON REQUEST.

Just add the light color code to P/N.

Example: 2x33W wide 90° without through-wiring/with 5000K Ra>80: 9300175w850

Light colors differing from standard require longer delivery times.
Photometric data is based on light color 840.

COMPLEMENTARY CODES FOR THROUGH-WIRING

Without through-wiring
2x1,5 mm²; for DALI 2x1,5 mm² + 2x1,5 mm²
2x2,5 mm²; for DALI 2x2,5 mm² + 2x1,5 mm²
3x1,5 mm²; for DALI 3x1,5 mm² + 2x1,5 mm²
3x2,5 mm²; for DALI 3x2,5 mm² + 2x1,5 mm²
4x1,5 mm²; for DALI 4x1,5 mm² + 2x1,5 mm²
4x2,5 mm²; for DALI 4x2,5 mm² + 2x1,5 mm²
5x1,5 mm²; for DALI 5x1,5 mm² + 2x1,5 mm²
5x2,5 mm²; for DALI 5x2,5 mm² + 2x1,5 mm²

Digit

* = 0
* = 1
* = 2
* = 3
* = 4
* = 5
* = 6
* = 7
* = 8






WHY APOLLO G2 INDUSTRY?



INDUSTRIAL LED BOARD
INDUSTRIAL CONVERTER




Longer lifetime,
less maintenance,
higher ambient temperature



Protection class I
Ingress Protection IP65

Dust-tight, water jet proof, 220-240V 50/60Hz, *registered



LUNA

PRO | PRO INDUSTRY | XLS

HOUSING Polycarbonate, impact-resistant, IK08.

LAMP COVER Polycarbonate with integrated LED unit.

SEALS Ageing-resistant silicone seals.



ELECTRICAL COMPONENTS High power LEDs, LED converter.

ASSEMBLY Variable mounting distances due to PRACHT-CLIP-SYSTEM. Suitable for ceiling, vertical wall, pendant and rail mounting.

FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 fluorescent light-exchange, logistic halls, warehouse areas, technical facility rooms.

INTEGRATED LED

The LEDs are integrated in the reflector. Particularly fast and safe connection. Homogeneous light emission.



ROBUST MATERIALS

Housing made of impact resistant polycarbonate IK08.

SUITABLE CABLE ENTRY

The cable entry can be on the front or back side. ESD protected installation




IP 65

Tight thanks to high quality all-round silicone seal and strong clamps.




SECURE MOUNTING

Suitable for all situations. Pendant, ceiling and wall mounting. Variable mounting distances.



CLOSURES

High-quality stainless steel toggle latches without sharp edges.



FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

**FOR EVERYDAY
LIFE**
Cost-effective and
easy to assemble

BASIC LINE

**FOR PRO-
FESSIONALS**
Industrial quality with
5 year PRACHT warranty

PRO LINE

**FOR THE
EXTREME**
Customised solutions &
highest requirements

5

**YEAR
WARRANTY**



**UP TO 100.000 h
LIFETIME**



**ENERGY
EFFICIENCY
CLASS**

IP65



**FROM -25 °C TO +40 °C
DEPENDENT ON MODEL**

LUNA PRO

R_a > 80, color temperature 4000 K, light distribution 120° wide beam, Ta: -20°C ... +35°C.

ON/OFF	P/N	Power	Luminous flux	Length	XLS Code		XLS C Master	
					P/N		P/N	
	5291004	1x22 W	2800 lm	1200 mm	-		-	
	5291005	1x31 W	3800 lm	1500 mm	-		-	
	5291014	1x43 W	5400 lm	1200 mm	-		-	
DIM-DALI	5291015	1x52 W	6500 lm	1500 mm	-		-	
	5291009	1x22 W	2800 lm	1200 mm	DIM-Casambi	5291009x00	5291009x01	
	5290100	1x31 W	3800 lm	1500 mm		5291000x00	5291000x01	
	5291019	1x43 W	5400 lm	1200 mm		5291019x00	5291019x01	
	5291010	1x52 W	6500 lm	1500 mm		5291010x00	5291010x01	

LUNA PRO INDUSTRY

R_a > 80, color temperature 4000 K, light distribution 120° wide beam, Ta: -20°C ... +35°C, with industry converter.

P/N	Power	Luminous flux	Length	XLS Code		XLS C Master	
				P/N		P/N	
5291104	1x23 W	2800 lm	1200 mm	-		-	
5291105	1x33 W	3800 lm	1500 mm	-		-	
5291114	1x43 W	5400 lm	1200 mm	-		-	
5291115	1x52 W	6500 lm	1500 mm	-		-	
5291135	1x75 W	11000 lm	1500 mm	-		-	
5291009	1x23 W	2800 lm	1200 mm	DIM-Casambi	5291109x00	DIM-Casambi	5291109x01
5290100	1x33 W	3800 lm	1500 mm		5291100x00		5291100x01
5291019	1x43 W	5400 lm	1200 mm		5291119x00		5291119x01
5291010	1x52 W	6500 lm	1500 mm		5291110x00		5291110x01
5291130	1x75 W	11000 lm	1500 mm		5291130x00		5291130x01

ACCESSORIES

Through-wiring	P/N
3x1,5mm² Set LUNA PRO 1,2m, consisting of rigid cable, 1x3pol terminal block one-sided	5552132
3x1,5mm² Set LUNA PRO 1,5m, consisting of rigid cable, 1x3pol terminal block one-sided	5552135
5x2,5mm² Set LUNA PRO 1,2m, consisting of rigid cable, 2x5pol terminal block	5552152
5x2,5mm² Set LUNA PRO 1,5m, consisting of rigid cable, 2x5pol terminal block	5552155


NOTE

With XLS C (Extended Lighting Solutions), the use of CASAMBI results in a powerful and individually scalable lighting control. CASAMBI is an intelligent technology and communicates via a radio system based on Bluetooth Low Energy. This technology enables to connect up to 127 subscribers via a meshed network. The administration takes place via app by smartphone, smartwatch or tablet and can also be used externally addressed and operated via remote access. Also available with integrated emergency lighting module or rechargeable battery on request.



NOTE

OTHER LIGHT COLORS AVAILABLE ON REQUEST.
Light color: 830, 850, 865 Please add the LC code to P/N. Example: 1x54W, wide 120°, without through-wiring, with 4000K, Ra>80: 5291110850 Light colors differing from standard require longer delivery times. Photometric data is based on light color 840.



Protection class I
Ingress Protection IP65
220–240V 50/60 Hz,
*for basic type LUNA PRO ON/OFF



KATLA

INDUSTRY | REMADE | XLS | SKII


HOUSING Translucent, impact resistant opalized housing made of one piece (shatter proof polycarbonate or NAWAROH®), endcaps made of PBT (shatter proof) or REMADE.

SEALS Durable, short silicone seals (silicone free optionally available).

ELECTRICAL COMPONENTS High performance LED, LED converter. THROUGH-WIRING 3x1,5mm² factory-installed (exception XLS).

INSTALLATION Variable mounting points due to PRACHT-CLIP-SYSTEM. Easy access power supply spaces.


FIELDS OF APPLICATION Depending on model: Parking decks, basements, factories, service areas, logistics and production centers, service pits, technical and secondary rooms, unprotected outdoor areas.



INDUSTRY VERSION


Industry components - longer lifetime, low maintenance, real power

PRACHT®



CEILING ILLUMINATION

Say goodbye to dark multi-storey car park ceilings.



FAST INSTALLATION

Thanks to two spacious grid connection units.

SUSTAINABLE

Remade version - luminaire made from 99% recycled materials.



FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

FOR EVERYDAY LIFE
Cost-effective and easy to assemble

BASIC LINE

FOR PROFESSIONALS
Industrial quality with 5 year PRACHT warranty

PRO LINE

FOR THE EXTREME
Customised solutions & highest requirements

5

YEAR WARRANTY



UP TO 100.000 h LIFETIME



ENERGY EFFICIENCY CLASS



**FROM -20 °C TO +45 °C
DEPENDENT ON MODEL**

IP66

KATLA

Housing made of polycarbonate (shatter proof), Ta: -20°C ... +35°C, 4000K.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9131120	1x20 W	2800 lm	1205 mm	1,2 kg	3x1,5 mm²
	9131150	1x26 W	3800 lm	1465 mm	1,4 kg	3x1,5 mm²
	9131160	1x37 W	4900 lm	1465 mm	1,5 kg	3x1,5 mm²
DIM-DALI	9131180	1x52 W	6700 lm	1745 mm	1,7 kg	3x1,5 mm²
	9171168	1x22 W	2800 lm	1205 mm	1,4 kg	3x1,5 mm² + 2x1,5 mm²
	9171169	1x29 W	3800 lm	1465 mm	1,6 kg	3x1,5 mm² + 2x1,5 mm²
	9171269	1x40 W	4900 lm	1465 mm	1,6 kg	3x1,5 mm² + 2x1,5 mm²
	9171280	1x53 W	6700 lm	1745 mm	1,8 kg	3x1,5 mm² + 2x1,5 mm²

KATLA INDUSTRY

Housing made of polycarbonate (shatter proof), Ta: -20°C ... +45°C, 4000K.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9137334	1x39 W	5300 lm	1495 mm	1,3 kg	3x1,5 mm²
	9137374	1x52 W	6800 lm	1495 mm	1,5 kg	3x1,5 mm²
	9137355	1x53 W	7200 lm	1745 mm	1,5 kg	3x1,5 mm²
DIM-DALI	9137375	1x64 W	8500 lm	1745 mm	1,7 kg	3x1,5 mm²
	9137339	1x39 W	5300 lm	1495 mm	1,4 kg	3x1,5 mm² + 2x1,5 mm²
	9137379	1x52 W	6800 lm	1495 mm	1,6 kg	3x1,5 mm² + 2x1,5 mm²
	9137350	1x53 W	7200 lm	1745 mm	1,6 kg	3x1,5 mm² + 2x1,5 mm²
	9137370	1x64 W	8500 lm	1745 mm	1,8 kg	3x1,5 mm² + 2x1,5 mm²

KATLA SK II

Housing made of polycarbonate (shatter proof), Ta -20°C ... +30°C, 4000K.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9128123	1x23 W	2800	1205 mm	1,3 kg	2x1,5 mm²
	9128124	1x30 W	3700	1465 mm	1,3 kg	2x1,5 mm²
	9128134	1x37 W	4500	1465 mm	1,3 kg	2x1,5 mm²
DIM-DALI	9128135	1x39 W	4800	1745 mm	1,5 kg	2x1,5 mm²
	9128128	1x23 W	2800	1205 mm	1,3 kg	2x1,5 mm²
	9128129	1x30 W	3700	1465 mm	1,3 kg	2x1,5 mm²
	9128139	1x37 W	4500	1465 mm	1,3 kg	2x1,5 mm²
	9128130	1x39 W	4800	1745 mm	1,5 kg	2x1,5 mm²

KATLA XLS S

Housing made of polycarbonate (shatter proof), Ta: -20°C ... +35°C, 4000K, with HF-sensor.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9106120	1x20 W	2800	1205 mm	1,2 kg	-
	9106150	1x26 W	3800	1465 mm	1,4 kg	-
	9106160	1x37 W	4900	1465 mm	1,5 kg	-
	9106180	1x52 W	6700	1745 mm	1,7 kg	-

KATLA XLS C

Polycarbonate housing (impact-resistant), Ta: -20°C ... +35°C, 4000K, with PRACHT CONNECT MODULE for CASAMBI.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9171168x00	1x39 W	5300	1205 mm	1,40	3x1,5 mm²
	9171169x00	1x52 W	6800	1465 mm	1,60	3x1,5 mm²
	9171269x00	1x53 W	7200	1465 mm	1,60	3x1,5 mm²
DIM-DALI	9171280x00	1x64 W	8500	1745 mm	1,80	3x1,5 mm²
	9171168x01	1x39 W	5300	1205 mm	1,40	3x1,5 mm²+2x1,5 mm
	9171169x01	1x52 W	6800	1465 mm	1,60	3x1,5 mm²+2x1,5 mm
	9171269x01 A++	1x53 W	7200	1465 mm	1,60	3x1,5 mm²+2x1,5 mm
	9171280x01	1x64 W	8500	1745 mm	1,80	3x1,5 mm²+2x1,5 mm

KATLA REMADE

Housing opalized (shatter proof), Ta -20°C ... +35°C, 4000K.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9131121	1x20 W	2800 lm	1205 mm	1,2 kg	3x1,5 mm²
	9131151	1x26 W	3800 lm	1465 mm	1,4 kg	3x1,5 mm²
	9131161	1x37 W	4900 lm	1465 mm	1,5 kg	3x1,5 mm²
DIM-DALI	9131181	1x52 W	6700 lm	1745 mm	1,7 kg	3x1,5 mm²
	9131126	1x20 W	2800 lm	1205 mm	1,2 kg	3x1,5 mm² + 2x1,5 mm²
	9131156	1x29 W	3800 lm	1465 mm	1,4 kg	3x1,5 mm² + 2x1,5 mm²
	9171166	1x40 W	4900 lm	1465 mm	1,5 kg	3x1,5 mm² + 2x1,5 mm²
	9171186	1x53 W	6700 lm	1745 mm	1,7 kg	3x1,5 mm² + 2x1,5 mm²

KATLA REMADE SKII

Housing opalized (shatter proof), Ta -20°C ... +35°C, 4000K.

ON/OFF	P/N	Power	Luminous flux	Length	Weight	Through-Wiring
	9128623	1x23 W	2800 lm	1205 mm	1,3 kg	2x1,5 mm²
	9128624	1x30 W	3700 lm	1465 mm	1,3 kg	2x1,5 mm²
	9128634	1x37 W	4500 lm	1465 mm	1,3 kg	2x1,5 mm²
DIM-DALI	9128635	1x39 W	4800 lm	1745 mm	1,5 kg	2x1,5 mm²
	9128628	1x23 W	2800 lm	1205 mm	1,3 kg	2x1,5 mm²
	9128629	1x30 W	3700 lm	1465 mm	1,3 kg	2x1,5 mm²
	9128639	1x37 W	4500 lm	1465 mm	1,3 kg	2x1,5 mm²
	9128630	1x39 W	4800 lm	1745 mm	1,5 kg	2x1,5 mm²

Product-specific data under www.pracht.com



Front end cable entry




Spacious grid connection



Bolted components



Flat ceiling structure




Ceiling illumination



Variable mounting points



Protection class I and II
Ingress Protection IP66
Dust-tight, protected against water jets, 220-240V 50/60 Hz, *registered



TUBIS

N LED | LED INDUSTRY | LED RESISTENT

HOUSING Tubular housing, fully sealed made of PC (polycarbonate, shockproof), PO (PRACHTOPAL®, PMMA, impact-resistant), Silicate glass, substantially acid and alkali resistant, diameter 90 mm.

SEALS Short, ageing resistant silicone seals.


ELECTRICAL COMPONENTS High performance LED, built-in converter.

THROUGH-WIRING 5x2.5 mm² max. available, depending on model

INSTALLATION Variable fixing points thanks to PRACHT stainless steel clamps.

Suitable for ceiling, pendant, horizontal and vertical wall mounting.


FIELDS OF APPLICATION Unprotected outdoor areas, industrial and washing bays, high humidity areas.



MODEL INDUSTRY

Different light distributions.
Industry components-strong power.


PRACHT®



EASY EXCHANGE OF COMPONENTS

TUBIS N LED + LED INDUSTRY

- not glued
- sustainable.




IP 66/68/X9K

- Short sealing system
- wide application spectrum

COMPLETELY TIGHT.

TUBIS LED RESISTANT

- in electroplating or similar
- for environments contaminated with harmful gases (chlorine, sulphur, ammonia, etc.)



FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

FOR EVERYDAY LIFE

Cost-effective and easy to assemble

BASIC LINE

FOR PROFESSIONALS

Industrial quality with 5 year PRACHT warranty

PRO LINE

FOR THE EXTREME

Customised solutions & highest requirements

5

YEAR WARRANTY



UP TO 100.000 h LIFETIME

ENERGY EFFICIENCY CLASS

IP66
IP68
IPX9K



LIVESTOCK FARMING OPTIONAL



-30 °C TO +50 °C
DEPENDENT ON MODEL



UNPROTECTED OUTDOOR AREA

TUBIS N LED

LVK = 125°, Housing PO (PRACHTOPAL®, impact-resistant), Ta -20°C ...+35°C

Performance	Luminous flux	Length	Weight	On/Off P/N	DIM-DALI P/N	
1x17 W	2300 lm	700 mm	2,3 kg		72*3612	72*3617
1x20 W	2700 lm	700 mm	2,3 kg		72*3632	72*3637
1x31 W	4500 lm	1260 mm	3,5 kg		72*3614	72*3619
1x37 W	5400 lm	1260 mm	3,5 kg		72*3634	72*3639
1x39 W	5600 lm	1540 mm	4,0 kg		72*3615	72*3610
1x47 W	6700 lm	1540 mm	4,0 kg		72*3635	72*3630

NOTE	Please replace the * in the item no. with the corresponding number in the adjacent table!	COMPLEMENTARY CODES FOR THROUGH-WIRING Without through-wiring Through-wiring 3x1.5 mm² = 10A 3x1.5 (luminaire length + 25 mm) Through-wiring 3x2.5 mm², with DALI 3x2.5 mm2 + 2x2.5 mm2 5x1.5 mm² ; with DALI 3x1.5 mm² + 2x1.5 mm² (luminaire length + 25 mm) 5x2.5 mm² ; with DALI 3x2.5 mm² + 2x1.5 mm² (luminaire length + 25 mm)	Digit * = 0 * = 3 * = 4 * = 7 * = 8	Surcharge -- € applies applies applies applies

TUBIS LED INDUSTRY

PO cover (PRACHTOPAL®, impact-resistant), Ta -30°C ...+50°C, 4000K, various light distribution curves available.

Performance	Luminous flux	Length	Weight	LVK 125° On/Off	LVK 100° On/Off	LVK 80° On/Off	LVK 125° DIM-DALI	LVK 100° DIM-DALI	LVK 80° DIM-DALI
1x31 W	4600 lm	1260 mm	4,0 kg	7a*31424	7a*32424	7a*33424	7a*31429	7a*32429	7a*33429
1x36 W	5500 lm	1260 mm	4,0 kg	7a*31434	7a*32434	7a*33434	7a*31439	7a*32439	7a*33439
1x38 W	5800 lm	1540 mm	4,2 kg	7a*31425	7a*32425	7a*33425	7a*31420	7a*32420	7a*33420
1x43 W	6300 lm	1260 mm	4,0 kg	7a*31444	7a*32444	7a*33444	7a*31449	7a*32449	7a*33449
1x47 W	6900 lm	1540 mm	4,2 kg	7a*31435	7a*32435	7a*33435	7a*31430	7a*32430	7a*33430
1x52 W	7900 lm	1540 mm	4,2 kg	7a*31445	7a*32445	7a*33445	7a*31440	7a*32440	7a*33440
1x60 W	8400 lm	1260 mm	4,0 kg	7a*31454	7a*32454	7a*33454	7a*31459	7a*32459	7a*33459
1x74 W	10500 lm	1540 mm	4,2 kg	7a*31455	7a*32455	7a*33455	7a*31450	7a*32450	7a*33450

NOTE	Silicate glass and stainless steel end caps available on request.	Please replace the * in the item no. with the corresponding number in the adjacent table!	COMPLEMENTARY CODES FOR THROUGH-WIRING Without through-wiring Through-wiring 3x1.5mm²; with DALI 3x1.5mm² + 2x1.5mm² Through-wiring 3x2.5mm²; with DALI 3x2.5mm² + 2x2.5mm² Through-wiring 5x1.5mm² Through-wiring 5x2.5mm²	Digit * = 0 * = 3 * = 4 * = 7 * = 8	Surcharge -- € applies applies applies applies

TUBIS LED RESISTANT

PO housing (PRACHTOPAL®, impact-resistant), Ta -30°C ...+50°C, gas-tight bonded, with 1m connection cable.

Performance	Luminous flux	Länge	Net weight	On/Off P/N	Dali P/N				
				LVK 80°	LVK 100°	LVK 125°	LVK 80°	LVK 100°	LVK 125°
1x31 W	4600 lm	1260 mm	3,8 kg	7c*33-24	7c*32-24	7c*31-24	7c*33-29	7c*32-29	7c*31-29
1x36 W	5800 lm	1540 mm	4,0 kg	7c*33-25	7c*32-25	7c*31-25	7c*33-20	7c*32-20	7c*31-20
1x38 W	5500 lm	1260 mm	3,8 kg	7c*33-34	7c*32-34	7c*31-34	7c*33-39	7c*32-39	7c*31-39
1x43 W	6300 lm	1260 mm	3,8 kg	7c*33-44	7c*32-44	7c*31-44	7c*33-49	7c*32-49	7c*31-49
1x47 W	6900 lm	1540 mm	4,0 kg	7c*33-35	7c*32-35	7c*31-35	7c*33-30	7c*32-30	7c*31-30
1x52 W	7900 lm	1540 mm	4,0 kg	7c*33-45	7c*32-45	7c*31-45	7c*33-40	7c*32-40	7c*31-40
1x60 W	8400 lm	1260 mm	3,8 kg	7c*33-54	7c*32-54	7c*31-54	7c*33-59	7c*32-59	7c*31-59
1x74 W	10500 lm	1540 mm	4,0 kg	7c*33-55	7c*32-55	7c*31-55	7c*33-50	7c*32-50	7c*31-50

Please replace the item no. */- with the corresponding number in the adjacent table!	COMPLEMENTARY CODES FOR THROUGH-WIRING Without through-wiring 5x2.5 mm² ; with DALI 3x2.5 mm² + 2x2.5 mm² (luminaire length + 25 mm)	Digit * = 0 * = 8	Surcharge -- € applies	COMPLEMENTARY CODES FOR THROUGH-WIRING SK 1 Wielandstecker SK 1 offen SK 2 Wielandstecker SK2 offen	Digit ~ = 4 ~ = 3 ~ = 9 ~ = 8	Surcharge applies -- € applies -- €

PC-/REMADE Tubular housing

TUBIS LED INDUSTRY



PO-Tubular housing TUBIS

N LED and INDUSTRY



PO-Tubular housing

TUBIS N LED FARMER



Two point mounting



P/N 0694038 (V2A) | 0705040 (V4A) |
0694138CH (chlorine resistant)

Single point mounting

central fixing screw



P/N 0706041 (V2A) | 0706139 (V4A) |
0704045 (chlorine resistant)

Single point mounting

Lever release



P/N 0704047 (V4A)

Single-point mounting with

spring compensation



P/N 0706037 (V2A)

Pendulum installation



P/N 0698039 (V2A) | 0704048 (V4A) |
0704049 (chlorine resistant)

Pendulum installation

with steel cable



P/N 0706040 (V2A)

ACCESSORIES



There is always a set of two point mounting clamps included. At least two clamps per luminaire are always required!

Specification	1.4301 (V2A) P/N	1.4571 (V4A) P/N	1.4529 (chlorine resistant) P/N
Two point mounting	0694038	0705040	0694138CH
Single point mounting, central fixing screw	0706041	0706139	0704045
Single point mounting, central fixing screw, Lever release	-	0704047	-
Single point mounting, central fixing screw, Lever release , counterbalancing spring	0706037	-	-
Pendulum mounting	0698039	0704048	0704049
Pendulum installation set (2 clamps), for pendulum mounting with 2m steel cable	0706040	-	-



Protection Class I
Ingress protection IP68/IPX9K

Dusttight, water pressure tight, 230V/50 Hz *application pending



TROJA

G2 | MEDIENKANAL G2 | SKII

HOUSING Flat, made of stable aluminium (white, powder coated), vandalism protected, integrated ceiling/wall cable conduit.

LAMP COVER Made of polycarbonate (PC, shatter proof), opalised, bordered in aluminium profile frame, end caps made of die cast aluminium, optional Torx, Torx-TR (with pin) or individual safety lock.


SEALS Ageing resistant silicone seals.

THROUGH-WIRING Max. 5x2,5 mm² + DALI available.

INSTALLATION Process-safe assembly due to PRACHT EASY CONNECT (PEC) System - LED board is integrated in lamp cover. Simple plugging for ESD protected mounting.

FIELDS OF APPLICATION Vandalism endangered areas, underpasses, public areas, traffic installations, railway stations, prisons.


OPTION Media channel, Graffiti-Protect-System, other light



TOUGH

Vandalism protected up to 100 Joule IK10+ and anti graffiti protection (optional)

PRACHT®



PRACHT EASY CONNECT (PEC) SYSTEM

ESD Protection for LED by PEC System. Even faster and safer.


MODULAR

All-in-one solution — luminaire, motion sensor, speaker etc. There's room for everything in the media channel.



MEDIA CHANNEL

Simple installation - 3 separate channels for separate cable ducts.



5

YEAR
WARRANTY



UP TO 100.000 h
LIFETIME



ENERGY
EFFICIENCY
CLASS

100
JOULE

VANDALISM
PROTECTED, IK10+



FROM -25 °C TO +40 °C
DEPENDENT ON MODEL

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

FOR EVERYDAY
LIFE
Cost-effective and
easy to assemble

BASIC LINE

FOR PRO-
FSSIONALS
Industrial quality with
5 year PRACHT warranty

PRO LINE

FOR THE
EXTREME
Customised solutions &
highest requirements

TROJA G2 SKII

4000K, Ra90, RAL9010, single luminaire suitable for mounting on media channel, PCII.

Power	Luminous flux	Length	Weight	ON/OFF 110° P/N	DIM-DALI 110° P/N	ON/OFF ASYM P/N	DIM-DALI ASYM P/N
1x18 W	1800 lm	705 mm	4 kg	76*36121	76*36171	76*36126	76*36176
1x23 W	2200 lm	705 mm	4 kg	76*36221	76*36271	76*36226	76*36276
1x26 W	2600 lm	705 mm	4 kg	76*36321	76*36371	76*36326	76*36376
1x35 W	3300 lm	705 mm	4 kg	76*36521	76*36571	76*36526	76*36576
1x31 W	3300 lm	1261 mm	7 kg	76*36141	76*36191	76*36146	76*36196
1x43 W	4400 lm	1261 mm	7 kg	76*36241	76*36291	76*36246	76*36296
1x51 W	5100 lm	1261 mm	7 kg	76*36341	76*36391	76*36346	76*36396
1x65 W	6500 lm	1261 mm	7 kg	76*36541	76*36591	76*36546	76*36596
1x40 W	4300 lm	1561 mm	9 kg	76*36151	76*36101	76*36156	76*36106
1x52 W	5500 lm	1561 mm	9 kg	76*36251	76*36201	76*36256	76*36206
1x62 W	6400 lm	1561 mm	9 kg	76*36351	76*36301	76*36356	76*36306
1x66 W	7000 lm	1561 mm	9 kg	76*36551	76*36501	76*36556	76*36506

TROJA G2 SKII

4000K,Ra90, RAL9010, single luminaire suitable for mounting on media trunking, PC II.
With additional overvoltage protection and inrush current limiter.

Power	Luminous flux	Length	Weight	ON/OFF 110° P/N	DIM-DALI 110° P/N	ON/OFF ASYM P/N	DIM-DALI ASYM P/N
1x18 W	1800 lm	705 mm	4 kg	76*37121	76*37171	76*37126	76*37176
1x23 W	2200 lm	705 mm	4 kg	76*37221	76*37271	76*37226	76*37276
1x26 W	2600 lm	705 mm	4 kg	76*37321	76*37371	76*37326	76*37376
1x35 W	3300 lm	705 mm	4 kg	76*37521	76*37571	76*37526	76*37576
1x31 W	3300 lm	1261 mm	7 kg	76*37141	76*37191	76*37146	76*37196
1x43 W	4400 lm	1261 mm	7 kg	76*37241	76*37291	76*37246	76*37296
1x51 W	5100 lm	1261 mm	7 kg	76*37341	76*37391	76*37346	76*37396
1x65 W	6500 lm	1261 mm	7 kg	76*37541	76*37591	76*37546	76*37596
1x40 W	4300 lm	1561 mm	9 kg	76*37151	76*37101	76*37156	76*37106
1x52 W	5500 lm	1561 mm	9 kg	76*37251	76*37201	76*37256	76*37206
1x62 W	6400 lm	1561 mm	9 kg	76*37351	76*37301	76*37356	76*37306
1x66 W	7000 lm	1561 mm	9 kg	76*37551	76*37501	76*37556	76*37506

TROJA G2 ACCESSORIES

P/N	Description
0601661	Steel angle bracket for 45° luminaire corner mounting.

TROJA G2 LIGHT COLORS

Standard light colors 4000K for class I and class II. (Other light colors available on request)


Version	Light colors
SKII	R _a > 90: 3000K, 4000K (standard), 5000K

NOTE

Longer delivery times are to be expected for light colors that deviate from the standard. Photometric data for PC I is based on LF 840, for PC II on LF 940.

Please replace the * in the item no. with the corresponding

EXPLANATION FOR ORDERING OF THROUGH-WIRING		Digit	Price
	Without through-wiring	* = 0	
SKII	2x1,5 mm²; and DALI 2x1,5 mm² + 2x1,5 mm²	* = 1	applies
	2x2,5 mm²; and DALI 2x2,5 mm² + 2x1,5 mm²	* = 2	applies
	4x1,5 mm²; and DALI 4x1,5 mm² + 2x1,5 mm²	* = 5	applies
	4x2,5 mm²; and DALI 4x2,5 mm² + 2x1,5 mm²	* = 6	applies



TROJA MEDIENKANAL G2

Powder-coated RAL9010.


P/N	Description
0600705	TROJA MEDIA CHANNEL G2, Height 32mm, basic channel 1m.
0600706	TROJA MEDIA CHANNEL G2, Height 32mm, basic channel 2m.
0600707	TROJA MEDIA CHANNEL G2, Height 32mm, basic channell 3m.
0600710	Cover profile/blind field MEDIA CHANNEL G2, basic length 1m.
0600711	Cover profile/blind field MEDIA CHANNEL G2, basic length 2m.
0600712	Cover profile/blind field MEDIA CHANNEL G2, basic length 3m.

ACCESSORIES MEDIA CHANNEL G2

Art. Nr.	Beschreibung
0601652	Connector MEDIA CHANNEL G2 basic profile incl. screw
0601655	Cable bracket (aluminium) incl. mounting set
0601653	Mounting bracket for blind covering incl. accessories
0705854	End cap for basic profile MEDIA CHANNEL G2 incl. mounting accessories, aluminium, powder-coated RAL9010
0705855	End cap for MEDIA CHANNEL G2 incl. blind covering, incl. mounting accessories, aluminium, powder-coated RAL9010
0601722	Steel angle bracket for 45° media channel corner mounting, Initial/End piece closed, powder-coated RAL9010
0601721	Steel angle bracket for 45° media channel corner mounting, centerpiece cable duct at least 1 angle per basic profile, galvanized



Protection class I according to VDE 0711/EN 60598
Ingress protection IP65, class I and class II
Dustproof, water jet proof, 230W/50Hz,*registered



QUADRONIUS

**FOOD | SPORT | WET | POOL
HT | INDUSTRY**

HOUSING Die cast aluminium, white coating.

LAMP COVER Tempered glass, polycarbonate (PC, shatter proof), PMMA prism or PC prism.

SEALS Short, ageing-resistant silicone seals.

ELECTRICAL COMPONENTS High performance LED, converter.

INSTALLATION Pendant mounting, direct ceiling or wall mounting with ceiling mounting bracket (accessories).


OPTIONS Other housing color, four-lamp version, emergency light function, daylight and motion control sensor.

FIELDS OF APPLICATION Logistic centers, industrial halls, cold storage facilities (-40°C), high-rack warehouses.

Optional: Unprotected outdoor areas, sports halls, high ambient temperature, livestock farming, swimming pools.


EXCHANGEABLE COMPONENTS

Sustainable: not glued, thus no throw-away product.



THERMALLY DECOUPLED

Decoupled construction for optimum airflow distribution.




EIGHT DIFFERENT OPTICS

For perfect illumination.

HIGH-GRADE HOUSING

Die cast aluminium cooling ribs for intensive cooling.



FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

**FOR EVERYDAY
LIFE**
Cost-effective and
easy to assemble

BASIC LINE

**FOR PRO-
FESSIONALS**
Industrial quality with
5 year PRACHT warranty

PRO LINE

**FOR THE
EXTREME**
Customised solutions &
highest requirements

5

YEAR
WARRANTY



UP TO 100.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS

IP66



UNPROTECTED
OUTDOOR AREA
OPTIONAL




-40°C TO +75°C
(DEPENDENT ON MODEL)

MODELS


Standard	Standard version suitable for many areas - logistics to industry and cold storage facilities or agriculture. Inclusive 2.000 mm adjustable wire pendant suspension.	-	-	
SPORT	Safe to use in gymnasiums because of the shatter proof PC prismatic pane (luminous flux reduced by max 30% to standard) and ball-proof mounting bracket.	89,00 €	89,00 €	
WET	Wind and weatherproof with additional cover and climate screw connection, without fastening accessories.	109,00 €	218,00 €	
POOL	Withstands aggressive vapors thanks to special components and coatings for chlorine environments. With PMMA prismatic pane (luminous flux reduced by max 10% to standard), without mounting accessories.	295,00 €	549,00 €	
FOOD	Hygienic, low maintainance and a dustproof PC pane –designed for the foodstuff and beverage industry.	-	-	
INDUSTRY	Always DIM Dali, at 50°C ambient temperature L90B10 > 100.000 hours. Line filter according to highest industrial standard.	-	-	
HT	Ideal thermal management and selected component for properly high temperature, up to +75°.	-	-	

QUADRONIUS Single-lamp, 4000k, incl. 2.000 mm pendant mounting, 288 mm length. On/Off: Ta: -30°C...+45°C mm, 5,7kg. DIM-DALI: Ta: -30°C


ON/OFF	Optics	Power	Luminous flux	P/N	SPORT	WET	POOL	FOOD
	Wide 120°	1x97 W	15000 lm	86040101	-	86070101	86060101	86030101
	Wide 90°	1x97 W	15000 lm	86140101	-	86170101	86160101	86130101
	Medium 60°	1x97 W	15000 lm	86240101	-	86270101	86260101	86230101
	Deep 30°	1x97 W	15000 lm	86340101	-	86370101	-	86330101
	Asymmetric 60°	1x97 W	15000 lm	86540101	-	86570101	-	86530101
	Wide 120°	1x137 W	20000 lm	86040201	86050201	86070201	86060201	86030201
	Wide 90°	1x137 W	20000 lm	86140201	86150201	86170201	86160201	86130201
	Medium 60°	1x137 W	20000 lm	86240201	86250201	86270201	86260201	86230201
	Deep 30°	1x137 W	20000 lm	86340201	-	86370201	-	86330201
DIM-DALI	Asymmetric 60°	1x137 W	20000 lm	86540201	-	86570201	-	86530201
	Asymetrisch medium	1x143 W	15400 lm	85442001	84432001	86472001	84422001	85412001
	Extremly asymmetric	1x143 W	15000 lm	85842001	-	-	84822001	-
	Wide 120°	1x97 W	15000 lm	86040121	-	-	86060121	86030121
	Wide 90°	1x97 W	15000 lm	86140121	-	-	86160121	86130121
	Medium 60°	1x97 W	15000 lm	86240121	-	-	86260121	86230121
	Deep 30°	1x97 W	15000 lm	86340121	-	-	-	86330121
	Asymmetric 60°	1x97 W	15000 lm	86540121	-	-	-	86530121
	Wide 120°	1x137 W	20000 lm	86040221	86050221	-	86060221	86030221
	Wide 90°	1x137 W	20000 lm	86140221	86150221	-	86160221	86130221
	Medium 60°	1x137 W	20000 lm	86240221	86250221	-	86260221	86230221
	Deep 30°	1x137 W	20000 lm	86340221	-	-	-	86330221
	Asymmetric 60°	1x137 W	20000 lm	86540221	-	-	-	86530221
	Asymmetric medium	1x139 W	15400 lm	85442021	-	-	-	-
	Extremly asymmetric	1x139 W	15000 lm	85842021	-	-	-	-
	Asymmetric medium	1x143 W	15400 lm	-	84432021	-	84422021	85412021
	Extremly asymmetric	1x143 W	15000 lm	-	-	-	84822021	-



Deep 30°




High-Rack Optics




Asymmetrical Area




Wide beam 120°




Wide beam 65°



Wide beam 90°



Extremely asymmetric



Extremely asymmetric

Product specific
data under
www.pracht.com

QUADRONIUS

Two-lamp, 4000k, incl. 2.000 mm cable pendant. On/Off: Ta: -30°C...+45°C, 11,6 kg, 605 mm length. DIM-DALI: Ta: -40°C ...+45°C, 13,6kg, 768 mm length

ON/OFF	Optics	Power	Luminous flux	Standard	SPORT	POOL	FOOD
	Wide 120°	2x97 W	30000 lm	86040601	-	86260601	86030601
	Wide 90°	2x97 W	30000 lm	86140601	-	86160601	86130601
	Medium 60°	2x97 W	30000 lm	86240601	-	86260601	86230601
	Deep 30°	2x97 W	30000 lm	86340601	-	-	86330601
DIM-DALI	Wide 120°	2x137 W	40000 lm	86040701	-	86060701	86030701
	Wide 90°	2x137 W	40000 lm	86140701	-	86160701	86130701
	Medium 60°	2x137 W	40000 lm	86240701	-	86260701	86230701
	Deep 30°	2x137 W	40000 lm	86340701	-	-	86330701
	Wide 120°	2x97 W	30000 lm	86040621	-	86060621	86030621
	Wide 90°	2x97 W	30000 lm	86140621	-	86160621	86130621
	Medium 60°	2x97 W	30000 lm	86240621	-	86260621	86230621
	Deep 30°	2x97 W	30000 lm	86340621	-	-	86330621
	Wide 120°	2x137 W	40000 lm	86040721	86050721	86060721	86030721
	Wide 90°	2x137 W	40000 lm	86140721	86150721	86160721	86130721
	Medium 60°	2x137 W	40000 lm	86240721	86250721	86260721	86230721
	Deep 40°	2x137 W	40000 lm	86340721	-	-	86330721

ACCESSORIES

Description	P/N
Wall/ceiling mounting bracket single-lamp	06011071
Ceiling mounting bracket twin-lamp	06011081
Wall/ceiling mounting bracket single-lamp for model "POOL"	06012171
Ceiling mounting bracket twin-lamp for model „POOL“	06012181

QUADRONIUS INDUSTRY

DIM-DALI 4000k, incl. 2.000 mm pendant mounting, Ta: -40°C...+50°C mm, single-lamp: 457 mm length, 7,7 kg. Twin-lamp: 912 mm length, 15,5 kg.

Optics	P/N single-lamp	Power	Luminous flux	P/N twin-lamp	Power	Luminous flux
Wide 120°	86080221	1x134	14800 lm	86080621	2x134	29600 lm
Deep 25°	86280221	1x134	14900 lm	86280621	2x134	29700 lm
Medium 65°	86380221	1x134	15000 lm	86380621	2x134	29900 lm
Asymmetric medium	86480221	1x134	14500 lm	-	-	-
HRO	86580221	1x134	14300 lm	-	-	-

QUADRONIUS HT

DIM-DALI 4000k, incl. 2.000 mm pendant mounting, Ta: -40°C...+75°C mm, single-lamp: 457 mm length, 7,7 kg. Twin-lamp: 912 mm length, 15,5 kg.

Optics	P/N single-lamp	Power	Luminous flux	P/N twin-lamp	Power	Luminous flux
Breit 110°	86790121	1x119	13600 lm	86790521	2x119	27100 lm
Tief 40°	86890121	1x119	13100 lm	86890521	2x119	26200 lm

NOTE

OTHER LIGHT COLORS AVAILABLE ON REQUEST.

97W + 137W = 830, 840, 850 139W + 143W = 827, 830, 840, 730, 740, 757, 765 Industry + HT = 827, 830, 840, 850, 730, 740, 757, 765

Please add LC-Code to P/N.

Example: 86040101**830**

Longer delivery times can be expected in case of divergent light colors. Lighting data is based on LC 840.



Protection Class I in accordance with VDE 0711/EN

60598, Ingress protection IP66

Dustproof, water jet proof, 220–240V, 50/60Hz, * up to +60°C



GECKO L

EX-PROOF LUMINAIRES ZONES 1-21 & 2-22

HOUSING Durable, glass fiber reinforced polyester.


LAMP COVER Polycarbonate, impact-resistant, IK10.

SEALS Age-resistant silicone seals, sealed construction.

ELECTRICAL COMPONENTS Certified LED components and LED converters.

MOUNTING Suitable for pendant, ceiling, wall (vertical, horizontal and swivel) and pipe mounting. Accessories available separately. Each luminaire comes with 2 cable glands for secure in/out wiring.


APPLICATION AREAS Suitable for areas in which hazardous explosive atmospheres can occur, such as industry, refinery, in the oil and gas industry, open-cast mining, etc. Ambient temperature -30°... +55°C.



VERSATILE

In-out wiring available ex works.

PRACHT®



FLEXIBLE

Various mounting options optionally available as accessories


ROBUST MATERIALS

IK10 impact resistant.



EX-PROOF

Adapted to the challenges in hazardous areas.



5

YEAR
WARRANTY



UP TO 100.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS

IP66



EX
PROOF

IECEX

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

**FOR EVERYDAY
LIFE**
Cost-effective and
easy to assemble

BASIC LINE

**FOR PRO-
FESSIONALS**
Industrial quality with
5 year PRACHT warranty

PRO LINE

**FOR THE
EXTREME**
Customised solutions &
highest requirements

ZONE 1-21

Single luminaire, colour temperature 4000 K, Ra>80, IP66*

P/N without TW	P/N TW 5 x 2,5 mm²	Light distribution	Length	Luminous flux	Output	Efficiency
5281112	5282112	120° wide	670 mm	2600 lm	21 W	124 lm/W
5281104	5282104	120° wide	1278 mm	3800 lm	28 W	136 lm/W
5281114	5282114	120° wide	1278 mm	4800 lm	35 W	137 lm/W
5281124	5282124	120° wide	1278 mm	6800 lm	52 W	131 lm/W


ZONE 2-22

Single luminaire, colour temperature 4000 K, Ra>80, IP66*


P/N without TW	P/N TW 5 x 2,5 mm²	Light distribution	Length	Luminous flux	Output	Efficiency
5281212	5282212	120° wide	670 mm	2700 lm	18 W	150 lm/W
5281204	5282204	120° wide	1278 mm	2800 lm	18 W	156 lm/W
5281214	5282214	120° wide	1278 mm	5500 lm	36 W	153 lm/W
5281224	5282224	120° wide	1278 mm	6600 lm	43 W	153 lm/W

ACCESSORIES

EX55001	Ceiling mounting bracket set V2A
EX55002	Wall and ceiling mounting bracket set, swiveling
EX55003	Pendulum mounting set ring eye M8
EX55004	Pipe clamp 1 1/2" incl. screw M8
EX55005	Pipe clamp 2" incl. screw M8




Ceiling mounting bracket set V2A




Wall and ceiling mounting bracket set, swiveling



Mounting bracket set, swiveling
Pendulum mounting set ring



Pipe clamp 1 1/2" + 2" incl. screw M8



Gecko L 2-22 carries the following IECEx classifications:

Ex ec IIC T5 Gc
Ex tc IIIC T70°C Dc

Ambient temperature: -30°C ... +55°C

Contact ADLT for additional information.

Gecko L 1-21 carries the following IECEx classifications:

Ex eb mb IIC T5 Gb
Ex tb IIIC T80°C Db

Ambient temperature: -30°C ... +55°C

Contact ADLT for additional information.

IECEx

Protection class I
Ingress Protection IP66
220-240V 50/60 Hz



LTEC/LTAC

LIGHTING TRUNKING SYSTEM


HOUSING Stable high rigidity steel sheet track system with integrated cables.

LTEC with 4 conductors + PE, LTSC with 6 conductors + PE, LTAC with 10 conductors + PE.

SEALS Durable seals, IP55 protected. Meets the requirements of the sprinkler test (90 min).


INSTALLATION Fast mounting with variable mounting points.

FIELDS OF APPLICATION Storage facilities, logistic centers, industrial halls, cold storages, workshops.




MODULAR

The tapping points are at a distance of 1 metre - the the lights can be set according to the the lighting situation!




EASY INSTALLATION

PRO LINE luminaires are equipped with pre-installed connecting cables and adapters - plug and ready.



TIME IS MONEY

Fast installation due to easy connection of the bars.



EASY LUMINAIRE MOUNTING

It's that easy. Mount the rail and fix the luminaires with clamps.

5

YEAR
WARRANTY



LONG
LIFETIME



SPRINKLERTEST
PASSED

IP55

FROM EVERYDAY TO EXTREME - THE RIGHT SEGMENT FOR EVERY REQUIREMENT

ECO LINE

BASIC LINE

PRO LINE

FOR EVERYDAY
LIFE

Cost-effective and
easy to assemble

FOR PRO-
FSSIONALS

Industrial quality with
5 year PRACHT warranty

FOR THE
EXTREME

Customised solutions &
highest requirements



LTEC - LIGHTING TRUNKING EASY CONNECT

P/N	Description
9711210	LTEC (Easy Connect) feed unit (left) small, 25A with end cover max. 4mm², PG 16 d=15mm, 3L+N+PE
9711215	LTEC (Easy Connect) feed unit (left) big, max. 10mm², PG 21 d=21mm, 3L+N+PE
9711220	LTEC (Easy Connect) feed unit (right) big, max. 10mm², PG 21 d=21mm, 3L+N+PE
9711130	LTEC (Easy Connect) mounting rail 3L+N+PE - 2m, 25A, mounting distance max. 3m
9711150	LTEC (Easy Connect) mounting rail 3L+N+PE - 3m, 25A, mounting distance max. 3m

LTSC - LIGHTING TRUNKING STANDARD CONNECT

P/N	Description
9711211	LTSC (Standard Connect) feed unit (left) big max.10mm², PG 21 d=21mm 3L+N+PE+2x0,75mm²
9711151	LTSC (Standard Connect) mounting rail 3L+N+PE - 3m, 25A, mounting distances max. 3m + outlet control line
9711131	LTSC (Standard Connect) mounting rail 3L+N+PE - 2m, 25A, mounting distances max. 3m + outlet control line
9711221	LTSC (Standard Connect) feed unit (right) big max.10mm², PG 21 d=21mm 3L+N+PE+2x0,75mm²

LTAC - LIGHTING TRUNKING ADVANCED CONNECT

P/N	Description
9712210	LTAC (Advanced Connect) feed unit (left) 25A mit Endabdeckung PE+Steuerleitung+2 Netze je 3L+N, max. 10mm², 2x PG 21 d=21mm
9712220	LTAC (Advanced Connect) feed unit (right) 25A mit Endabdeckung PE+Steuerleitung+2 Netze je 3L+N, max. 10mm², 2x PG 21 d=21mm
9712103	LTAC (Advanced Connect) mounting rail, PE + 2 Netze je 3L+N - 2m, 25A, Mounting distances max. 5m, 2+1 outlets, control cable one-sided
9712105	LTAC (Advanced Connect) mounting rail, PE + 2 Netze je 3L+N - 3m, 25A, Mounting distances max. 5m, 3+2 outlets, control cable one-sided

ACCESSORIES

P/N	Description
9711320	LTEC LTSC mounting bracket for lighting trunking with steelcord 3m
9712321	LTAC universal mounting bracket galvanized for luminaires or mounting rail
9711310	LTEC LTSC universal mounting bracket for luminaires or mounting rail
9711311	LTEC LTSC COMO universal mounting bracket for luminaires or mounting rail with enlarged hole
9711312	LTAC COMO universal mounting bracket for luminaires or mounting rail with enlarged hole
9713100	LTEC LTSC LTAC 10 A output adapter with variable phase tap for mounting on luminaires Cable SO5Z1Z1-F - 3x 1.5 mm² L+N+PE - 1 m - open cable ends
9713200	LTSC LTAC Output adapter 16 A, with variable phase tap L+N+PE
9713000	Control contact 2-pole for outgoing adapter LTSC LTAC (e.g. DALI)



LTEC | LTSC



LTEC




Open tap point



LTSC



LTSC



Feed unit



LTAC



LTAC



Protected tap point

NOTE


PRACHT Service - we prepare the PRO LINE luminaires thus far that the connection cable with adapter and the mounting brackets are delivered pre-assembled.

Please add the initials „EC“, „SC“ oder „AC“ to the luminaire P/N for pre-assembled delivery:

LTEC LTSC	Pre-assembly incl. output adapter 10 A and luminaire mounting clamp
LTAC	Pre-assembly incl. output adapter 10 A and luminaire mounting clamp
LTSC	Pre-assembly for DALI luminaires incl. output adapter 16 A, and luminaire mounting clamp
LTAC	Pre-assembly for DALI luminaires incl. output adapter 16 A, and luminaire mounting clamp



PRACHT®



INFINITY
ANY
LUMINAIRE
CAN TURN
INTO A
PRACHT
LUMINAIRE

Alfred PRACHT Lichttechnik GmbH | PRACHT Lighting Solutions GmbH
Am Seerain 3 | D-35232 Dautphetal-Buchenau/Lahn | Germany