


survivor 50 classic **naked**



IK17 - 175 joules impact resistance

IP66 - hermetically sealed light module cassette

AT06 - security torx tamper-proof fasteners

description

Heavy-gauge aluminium mounting bracket with durable polyester powder coat finish
Impact-resistant UV-stabilised high-transmission polycarbonate light module diffuser
Serviceable replaceable and upgradable light module cassette
Internal socket drive security-torx 304 stainless steel security fasteners
Integral energy efficient Zhaga compliant Tridonic LED modules and power supply unit
Direct-fix surface mounted
1.0 m circular flex connection

applications

extremely robust surface mounted luminaire that enhances safety and security in the most challenging environments. a durable construction ensures dependable operation and superior performance under harsh operating conditions; ideal for applications such as transportation, custodial, public areas, and secure healthcare

country of origin

Australia

accreditations

Australian Made and Owned
DALI alliance
EESS
RCM

warranty

7-year standard
10-year on application

standards

AS/NZS 60598.1:2017
AS/NZS 60598.2.1:2014
AS/NZS 60598.2.22:2019
AS/NZS 2293.3:2018
IEC/EN 62262:2002+A1:2021
AS 60529-2004
ANSI/IES LM-79-19
ANSI/IES LM-80-21
ANSI/IES TM-21-21

survivor 50 classic **naked**



options

finishes

black texture • white texture polyester powder coat
additional non-standard powder coat colours
35-year warranty powder coat on request

control system

DALI-2 • fixed output • Casambi wireless • switchDIM • 0-10 V

colour rendering index [CRI]

80+ • 90+

correlated colour temperature [CCT]

2700 K • 3000 K • 3500 K • 4000 K • 5000 K • 6500 K • tunable white

coloured LEDs

RGB • RGB+W • RGBW • RGBW+W • red • green • blue

electrical connection


IP68 quick-connect plug+socket • IP20 plug

sensors

type microwave • passive infrared
control system DALI-2 • Casambi wireless • basic on/off
detection mode presence • ambient light

emergency packs

type integrated
monitoring system DALI-2 • OEM proprietary
operating mode maintained • non-maintained • sustained



weights + dimensions [kg / mm]

nominal	L	W	H	weight
500	430	63	81	1.0
700	660	63	81	1.5
1000	940	63	81	2.1
1200	1220	63	81	2.7
1500	1500	63	81	3.3
1800	1780	63	81	4.0
2100	2060	63	81	4.8
2400	2340	63	81	5.5
2600	2620	63	81	6.0
2900	2900	63	81	6.7

integrated lighting systems

description

fully integrated and modular plug-n-play lighting systems for the most challenging and robust environments. every system is custom-manufactured in Australia using high-quality materials. supplied in pre-fabricated sections with pre-wired light module cassettes, and interconnecting IP68 quick-connect leads; making installation and maintenance effortless. available with multiple circuits, control systems, light sources, finishes, sensors, and emergency packs

sensors

type microwave • passive infrared
control system DALI-2 • Casambi wireless • basic on/off
detection mode presence • ambient light

emergency packs

type integrated
monitoring system DALI-2 • OEM proprietary
operating mode maintained • non-maintained • sustained

survivor 50 classic **naked**



CRI 80+ | CCT 3000 K | **830**

nominal length	20%		40%		60%		80%		100%	
	lumens	watts	lumens	watts	lumens	watts	lumens	watts	lumens	watts
500	270	2.5	540	5.0	800	7.5	1070	10.0	1340	12.5
700	540	5.0	1070	10.0	1600	15.0	2140	20.0	2670	25.0
1000	800	7.5	1600	15.0	2410	22.5	3210	30.0	4010	37.5
1200	1070	10.0	2140	20.0	3210	30.0	4280	40.0	5350	50.0
1500	1340	12.5	2670	25.0	4010	37.4	5350	49.9	6680	62.4
1800	1600	15.0	3210	30.0	4810	44.9	6420	59.9	8020	74.9
2000	1870	17.5	3740	35.0	5610	52.5	7490	70.0	9360	87.5
2400	2140	20.0	4280	40.0	6420	60.0	8560	80.0	10690	100.0
2600	2410	22.5	4810	45.0	7220	67.5	9630	90.0	12030	112.5
2900	2670	25.0	5350	50.0	8020	75.0	10700	100.0	13370	125.0

CRI 80+ | CCT 4000 K | **840**

nominal length	20%		40%		60%		80%		100%	
	lumens	watts	lumens	watts	lumens	watts	lumens	watts	lumens	watts
500	280	2.5	560	5.0	840	7.5	1120	10.0	1400	12.5
700	560	5.0	1120	10.0	1680	15.0	2240	20.0	2800	25.0
1000	840	7.5	1680	15.0	2520	22.5	3350	30.0	4190	37.5
1200	1120	10.0	2240	20.0	3360	30.0	4480	40.0	5600	50.0
1500	1400	12.5	2800	25.0	4200	37.4	5590	49.9	6990	62.4
1800	1680	15.0	3360	30.0	5040	44.9	6710	59.9	8390	74.9
2000	1960	17.5	3920	35.0	5870	52.5	7830	70.0	9790	87.5
2400	2240	20.0	4470	40.0	6710	60.0	8950	80.0	11180	100.0
2600	2520	22.5	5030	45.0	7550	67.5	10060	90.0	12580	112.5
2900	2800	25.0	5590	50.0	8380	75.0	11180	100.0	13970	125.0

photometric data is nominal and intended for general information purposes only. it is not to be relied upon nor used in place of photometry files issued by Survivor Lighting Pty Ltd
± 5% measurement uncertainty

